

# SAFETY DATA SHEET

# METACAULK® COVER GUARD™

Fire-rated gasket for electrical boxes

# Section 1 - Product and Company Information

Product Name

Metacaulk® Cover Guard™

**Product Codes** 

66265, 66266, 66270, 66272, 66274, 66276

Chemical Family

Organic/Inorganic

Use

Firestopping Material

Manufacturer's Name

The RectorSeal Corporation 2601 Spenwick Drive Houston, Texas 77055 USA

Date of Validation January 23, 2015

Date of Preparation February 27, 2012 **HMIS Codes** 

Health 1
Flammability 0
Reactivity 0
PPI B

Emergency Telephone No. Chemtrec 24 Hours (800)-424-9300 USA (703)-527-3887 International

Technical Service Telephone No. (800)-231-3345 or (713)-263-8001

# Section 2 - Hazards Identification

#### **GHS CLASSIFICATION**

#### **Physical Hazards:**

None

#### **Health Hazards**

Acute Toxicity:

Oral: Not Classified
Dermal: Not Classified
Inhalation: Not Classified

Skin Corrosion/Irritation: Not Classified

Serious Eye Damage/Eye Irritation: Not Classified Respiratory or Skin Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified

Carcinogenicity: Not Classified

Reproductive Toxicology: Not Classified

Target Organ Systemic Toxicity - Single Exposure: Not Classified Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

# **ENVIRONMENTAL HAZARDS**

Hazardous to the Aquatic Environment: Not Classified

Acute aquatic toxicity: Not Classified Chronic aquatic toxicity: Not Classified Bioaccumulation potential: Not Classified Rapid degradability: Not Classified

# GHS Label elements, including precautionary statements

Pictogram: None Signal Word: None

Hazard Statements:

None

**Precautionary Statements:** 

P102 - Keep out of reach of children.

P264 - Wash hands thoroughly after handling.

# **Summary Of Acute Hazards**

May cause skin irritation.

### **Route Of Exposure, Signs And Symptoms**

**INHALATION** 

Not a respiratory irritant.

**EYE CONTACT** 

Contact may cause eye irritation.

SKIN CONTACT

Contact may cause skin irritation.

**INGESTION** 

Possible irritation to mucous membranes of the mouth, throat, and stomach.

SUMMARY OF CHRONIC HAZARDS

None known.

# MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of the cured elastomer.

### Section 3 - Composition/Information on Ingredients

% by WT CAS No. INGREDIENT UNITS

None as defined by OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Section 4 - First Aid Measures

If inhaled: Not a respiratory irritant.

If on skin: Wash with soap and water. If irritation occurs, seek medical attention.

If in eyes: Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

If swallowed: If swallowed, call a physician immediately. Only induce vomiting at the instruction of

a physician. Never give anything by mouth to an unconscious person.

#### Section 5 - Fire Fighting Measures

# **Extinguishing Media**

Foam, dry chemical, carbon dioxide or water fog.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (SCBA) and other protective clothing.

Unusual Fire And Explosion Hazards: Fire conditions will activate product causing intumescence to occur.

#### Section 6 - Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up debris to prevent footing hazard.

# Section 7 - Handling and Storage

**Precautions To Be Taken In Handling And Storing:** Do not store near heat, sparks, or open flames.

Other Precautions: KEEP OUT OF REACH OF CHILDREN.

#### Section 8 - Exposure Controls/Personal Protection

Respiratory Protection (Specify Type): None required.

Ventilation - Local Exhaust: N/A

Special: N/A

Mechanical (General): N/A

Other: N/A

Protective Gloves: None required.

Eye Protection: None required.

Other Protective Clothing Or Equipment: None required.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating,

drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

# Section 9 - Physical and Chemical Properties

Boiling point: N/A

Specific gravity (H20 = 1): N/A

Vapor pressure (mmHg): N/A

Melting point: N/A

Vapor Density (Air = 1): N/A

Evaporation rate (Ethyl Acetate = 1): N/A

Appearance/Odor: Black/Mild odor

Solubility in water: Insoluble

Volatile Organic Compounds (VOC) Content

(theoretical percentage by weight): < 1% or < 10 g/L

Flash point: None

Lower explosion limit: None Upper explosion limit: None

# Section 10 - Stability and Reactivity

Stability: Stable

Conditions To Avoid: None.

Incompatibility (Materials To Avoid): None known.

Hazardous Decomposition Products: CO, CO, and fragmented hydrocarbons.

Hazardous Polymerization: Will not occur.

# Section 11 - Toxicology Information

#### **Chronic Health Hazards**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

**Toxicology Data** 

Ingredient Name

None

# Section 12 - Ecological Information

### **Ecological Data**

Ingredient Name: None

Food Chain Concentration Potential: N/A

Waterfowl Toxicity: N/A

BOD: N/A

Aquatic Toxicity: N/A

### Section 13 - Disposal Considerations

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with federal, state, and local regulation regarding pollution.

# Section 14 - Transportation Information

DOT: Non-regulated

Ocean (IMDG): Non-regulated

Air (IATA): Non-regulated

WHMIS (Canada): Non-regulated

### Section 15 - Regulatory Information

# **Regulatory Data**

Ingredient Name: None

SARA 313 N/A

TSCA Inventory All components listed

CERCLA RQ N/A RCRA Code N/A

# Section 16 - Other Information

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made.

Consult RectorSeal for further information: (713) 263-8001