



A CSW Industrials Company

## PRODUCT DATA SHEET

### CON-COIL™

Max strength, high foam condenser coil cleaner

#### Description

Con-Coil is an acid-based foaming brightener and cleaner that lifts obstructing contaminants such as bugs, cottonwood, grass, lint, dirt and oxides from coils, pushes contaminants and grease out of areas of the coil which are normally inaccessible, to where they can be rinsed away with low pressure water. Leaves aluminum surfaces clean in less than five minutes. Suitable for air cooled condenser coils and can be used for cleaning electronic air filters.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE



#### Directions for Use:

1. Appropriately dilute with water for economic use.  
**Extremely dirty coils** - 1 part CON-COIL to 3 parts water.  
**Moderately dirty coils** - 1 part CON-COIL to 4 parts water.  
**Lightly dirty coils** - 1 part CON-COIL to 6 parts water.
2. Shut off system.
3. Spray the diluted Con-Coil™ on accessible areas. Use a low pressure all plastic sprayer.
4. Wait 30 seconds and spray again.
5. To penetrate a multi-bank coil spray again in 2 minutes.
6. Allow 5 minutes for full cleaning action.
7. Rinse coils and surrounding area off with water.

#### Characteristics | Features

- Commercial strength
- Acid-based
- Biodegradable
- High foaming action
- Brightens and degreases
- Concentrated – dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but completely clean and free of particulate matter in less than 5 minutes
- Will not harm copper or aluminum

#### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
82651	Gallon (3.8 L)	4 Bottles	45	1.21

**Specifications**

Wt/Gal @ 77°F 9.34 lbs./gal.

Flash Point None

Color Pink

Shelf Life 3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

**DANGER!**

Causes severe skin burns and serious eye damage. Fatal if swallowed, in contact with skin or if inhaled. May be corrosive to metals.

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.**

**Contains: Phosphoric acid (CAS # 7664-38-2) and Ammonium bifluoride (CAS # 1341-49-7). Precautionary Statements PREVENTION:** Avoid backspray from wind or high pressure washers. Do not breathe dust/fume/gas/mist/vapors/ spray. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Keep only in original container. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/ eye protection/ face protection. In case of inadequate ventilation wear respiratory protection. **RESPONSE - IF SWALLOWED:** Immediately call a POISON CENTER/doctor. Rinse mouth. **IF ON SKIN (or hair):** Take off all contaminated clothing immediately. Rinse skin with water. Immediately call a POISON CENTER or doctor/physician. **SPECIFIC TREATMENT:** Apply iced 0.13% benzalkonium chloride soaks or 2.5% calcium gluconate gel to affected areas. Wash contaminated clothing before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. **SPECIFIC TREATMENT:** Administer oxygen then consider 2.5 calcium gluconate by nebulizer. Absorb spillage to prevent material damage. **STORAGE:** Store in a corrosive resistant steel triple rinse container (or equivalent) promptly after emptying. Store locked up. Store in a well-ventilated place. Keep container tightly closed. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

**Limited Warranty**

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50400-0420