SATCO NUVO

Project Name

ocation

Prepared By



Notes

rw1 04-14-2025 00:07

General	
Status	Active
Watts	70W
Incandescent Equivalent	250W
HID Equivalent	250W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	10500L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Width: 8 in. Height: 8 in. Depth: 10.75 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Working Voltage	Direct wire range voltage 100-277V
Operating Frequency	50/60Hz
Candlepower	3377
Dimming Note	Dimmable with optional modules
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Thermal Management	2 step thermal management: 1 - When the lamp body temperature is > 203F, the output of the lamps will reduce to 75 percent; 2 - When the driver temperature is >257F, the

Operating Temperature	-30C (-22F) to +60C (+140F)	
Physical		
MOL	11.59	
MOD	7	
Lens Finish	Clear	
Lens Material	Polycarbonate (PC)	
Housing Color	White	
Photocell or Sensor	Multiple Optional Sensors Available	
Weight (lb.)	2.43	

output of the lamps will reduce to 55 percent.

Additional Information		
Additional Info	80-954 - Dimmable via WiFi accessory; 80-955 - Hi-Pro Motion Sensor / PIR; 80-956 - Hi-Pro Photocell; 80-957 - Hi-Pro Motion Sensor / MW	
Rated For Enclosed Fixture	Yes	
IP Rating	IP64	
Specification Note	This is not to be used with a ballast	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5 Year Limited - Hi-Pro	

Compliance		
Safety Listing	cULus - Certified; cULus - Classified	
Location Rating	Damp	
DLC Approved	No	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
FCC Compliant	Yes	
SDS Sheet	LED Lamp	

