SATCO NUVO

Project Name

Prepared By 1000 TOP 1973 1.8.1 3000 DUCE а 1213 1.000 0000 2000 DUCE \$833 1180 0.010 3993 0000 -0----0 l 1023 DECE 1811 1.8.8 0000 1003 0000 \$811 1.8.8.8 0.0118 3001 IN OR 2211 10.00 0000 10.7 1000 100 0.00 A.

SATCO S28929 40W/LED/WP/CCT/E26/100-277V

Notes

General	
Status	Active
Watts	20W/30W/40W
Incandescent Equivalent	100W
HID Equivalent	175W
Volts	120V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	3200L/4700L/6000L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50-60Hz
Dimming Note	Dimmable only via the wattage/lumen selectable dial included on lamp
Power Factor	>0.9
Operating Position	Horizontal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +45C (+113F)
Physical	
MOL	7.8
MOD	3.62
Lens Material	Plastic
Housing Color	White
Weight (lb.)	1.65
	1.05
Additional Information	
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

