

Project Name

Location

Prepared By



## SATCO S28980

30W/LEDWP/CCT/E26/100-277V

### Notes

(www) 03-12-2023 00:44:58

### General

|                         |   |
|-------------------------|---|
| Status                  | Active                                    |
| Watts                   | 10W/20W/30W                               |
| Incandescent Equivalent | 50W-70W                                   |
| HID Equivalent          | 150W-175W                                 |
| Volts                   | 120V-277V                                 |
| Shape                   | Corncob                                   |
| Base                    | Medium                                    |
| ANSI Base               | E26                                       |
| Finish                  | White                                     |
| CCT (Kelvin)            | 3000K/4000K/5000K                         |
| Temperature             | Warm to Cool White                        |
| CRI                     | 80+                                       |
| Lumens                  | 1700L/3200L/4500L                         |
| Beam Spread             | 180                                       |
| Dimmable                | Yes-Dimmable                              |
| Hours Rated             | 50000                                     |
| Product Category        | Corncob                                   |
| Technology              | LED                                       |
| Min Compartment Size    | Length: 8 in. Width: 8 in. Height: 11 in. |
| Ballasting Requirements | Ballast Bypass                            |

### Electrical

|                       |  |
|-----------------------|--|
| Operating Frequency   | 50-60Hz  |
| Dimming Note          | Dimmable only via the wattage/lumen selectable dial included on lamp |
| Power Factor          | >0.9   |
| Operating Position    | Horizontal   |
| Surge Protection      | Built-in surge protection - 4KV                                      |
| Operating Temperature | -30C (-22F) to +45C (+113F)  |

### Physical

|               |         |
|---------------|---------|
| MOL           | 7       |
| MOD           | 3.62    |
| Lens Material | Plastic |
| Housing Color | White   |
| Weight (lb.)  | 1.45    |

### Additional Information

|                            |                                      |
|----------------------------|--------------------------------------|
| Rated For Enclosed Fixture | Yes                                  |
| IP Rating                  | IP64                                 |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Warranty                   | 5 Year Limited - Hi-Pro              |

### Compliance

|                      |   |
|----------------------|---|
| Safety Listing       | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating      | Damp  |
| DLC Approved         | No  |
| California Status    | Lawful for sale in California                         |
| Title 20 / 24 Status | Lawful for sale                                       |
| RoHS Compliant       | Yes   |
| FCC Compliant        | Yes   |
| SDS Sheet            | LED_Lamp  |