



**THE BRITELUX™ LAMP** series is 25 % brighter than conventional 130 volt lamps. They produce a crisp bright light that is comparable to krypton lamps. They are ideal for residential applications and available in a wide variety of shapes and wattages.

A19



A21



B10



BR30



BR40



G16.5



G25



G30



G40



R20



S11



# Britelux™ Lamps

| Order code                                           | Description                           | Watts<br>(W) | Base | Volts<br>(V) | Finish/<br>Colour | Average<br>life<br>(hrs) | Filament | Lumens<br>(lm) | Case<br>qty |
|------------------------------------------------------|---------------------------------------|--------------|------|--------------|-------------------|--------------------------|----------|----------------|-------------|
| <b>A19</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 4 1/4 in. (108 mm) LCL : 2 7/8 in. (73 mm)     |                                       |              |      |              |                   |                          |          |                |             |
| 50921                                                | 25A19/SW/1M/120V/STD BLX/2P (2 pack)  | 25           | E26  | 120          | Soft white        | 1000                     | C-9      | 220            | 120         |
| <sup>†</sup> 50103                                   | 40A19/SW/1M/120V/STD BLX/2P (2 pack)  | 40           | E26  | 120          | Soft white        | 1000                     | C-9      | 440            | 120         |
| <sup>†</sup> 50102                                   | 60A19/CL/1M/120V/STD BLX/2P (2 pack)  | 60           | E26  | 120          | Clear             | 1000                     | C-9      | 830            | 120         |
| <sup>†</sup> 50104                                   | 60A19/SW/1M/120V/STD BLX/2P (2 pack)  | 60           | E26  | 120          | Soft white        | 1000                     |          |                |             |
| <sup>†</sup> 50107                                   | 60A19/F/1M/120V/STD BLX/2P (2 pack)   | 60           | E26  | 120          | Frost             | 1000                     | C-9      | 830            | 120         |
| <sup>†</sup> 50876                                   | 100A19/SW/1M/120V/STD BLX/2P (2 pack) | 100          | E26  | 120          | Soft white        | 1000                     | C-9      | 1400           | 120         |
| <b>B10</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)    |                                       |              |      |              |                   |                          |          |                |             |
| 50522                                                | 25B10/CL/2M/E12/120V/STD BLX          | 25           | E12  | 120          | Clear             | 2000                     | CC-2V    | 220            | 120         |
| 50525                                                | 25B10/CL/2M/120V/STD BLX              | 25           | E26  | 120          | Clear             | 2000                     | CC-2V    | 220            | 120         |
| 50523                                                | 40B10/CL/2M/E12/120V/STD BLX          | 40           | E12  | 120          | Clear             | 2000                     | CC-2V    | 370            | 120         |
| 50526                                                | 40B10/CL/2M/120V/STD BLX              | 40           | E26  | 120          | Clear             | 2000                     | CC-2V    | 370            | 120         |
| 50524                                                | 60B10/CL/2M/E12/120V/STD BLX          | 60           | E12  | 120          | Clear             | 2000                     | C-7A/3   | 550            | 120         |
| <sup>†</sup> 50527                                   | 60B10/CL/2M/120V/STD BLX              | 60           | E26  | 120          | Clear             | 2000                     | C-7A/3   | 550            | 120         |
| <b>BR30</b>                                          |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 5 1/8 in. (130 mm) LCL : 3 11/32 in. (85 mm)   |                                       |              |      |              |                   |                          |          |                |             |
| 52002                                                | 65BR30/FL/2M/ES/120V/STD BLX          | 65           | E26  | 120          | Clear             | 2000                     | CC-6     | 620            | 60          |
| <b>G16.5</b>                                         |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)          |                                       |              |      |              |                   |                          |          |                |             |
| 50685                                                | 25G16.5/CL/2M/E12/120V/STD BLX        | 25           | E12  | 120          | Clear             | 2000                     | CC-2V    | 220            | 500         |
| 10270                                                | 25G16.5/WH/2M/E12/120V/STD BLX        | 25           | E12  | 120          | White             | 2000                     | CC-2V    | 180            | 120         |
| 50686                                                | 40G16.5/CL/2M/E12/120V/STD BLX        | 40           | E12  | 120          | Clear             | 2000                     | CC-2V    | 370            | 120         |
| 50687                                                | 40G16.5/WH/2M/E12/120V/STD BLX        | 40           | E12  | 120          | White             | 2000                     | CC-2V    | 330            | 120         |
| 50688                                                | 60G16.5/CL/2M/E12/120V/STD BLX        | 60           | E12  | 120          | Clear             | 2000                     | CC-2V    | 650            | 120         |
| 50689                                                | 60G16.5/WH/2M/E12/120V/STD BLX        | 60           | E12  | 120          | White             | 2000                     | CC-2V    | 580            | 500         |
| <sup>†</sup> 10159                                   | 60G16.5/WH/2M/120V/STD BLX            | 60           | E26  | 120          | White             | 2000                     | CC-2V    | 580            | 500         |
| <b>G25</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 4 1/2 in. (144 mm) LCL : 3 1/2 in. (77 mm)     |                                       |              |      |              |                   |                          |          |                |             |
| 50167                                                | 25G25/CL/2M/120V/STD BLX              | 25           | E26  | 120          | Clear             | 2000                     | CC-6     | 220            | 150         |
| 50168                                                | 25G25/WH/2M/120V/STD BLX              | 25           | E26  | 120          | White             | 2000                     | CC-6     | 200            | 60          |
| 50169                                                | 40G25/CL/2M/120V/STD BLX              | 40           | E26  | 120          | Clear             | 2000                     | CC-6     | 440            | 60          |
| 50170                                                | 40G25/WH/2M/120V/STD BLX              | 40           | E26  | 120          | White             | 2000                     | CC-6     | 400            | 60          |
| <b>G30</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 5 13/32 in. (137 mm) LCL : 3 9/32 in. (83 mm)  |                                       |              |      |              |                   |                          |          |                |             |
| 50180                                                | 40G30/CL/2M/120V/STD BLX              | 40           | E26  | 120          | Clear             | 2000                     | CC-6     | 440            | 100         |
| 50181                                                | 40G30/WH/2M/120V/STD BLX              | 40           | E26  | 120          | White             | 2000                     | CC-6     | 400            | 60          |
| <sup>†</sup> 50182                                   | 60G30/CL/2M/120V/STD BLX              | 60           | E26  | 120          | Clear             | 2000                     | CC-6     | 750            | 100         |
| <b>G40</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 6 15/16 in. (176 mm) LCL : 3 29/32 in. (99 mm) |                                       |              |      |              |                   |                          |          |                |             |
| 50173                                                | 40G40/CL/2M/120V/STD BLX              | 40           | E26  | 120          | Clear             | 2000                     | CC-6     | 440            | 24          |
| 50174                                                | 40G40/WH/2M/120V/STD BLX              | 40           | E26  | 120          | White             | 2000                     | CC-6     | 440            | 24          |
| 50175                                                | 60G40/CL/2M/120V/STD BLX              | 60           | E26  | 120          | Clear             | 2000                     | CC-6     | 520            | 24          |
| 50177                                                | 100G40/CL/2M/120V/STD BLX             | 100          | E26  | 120          | Clear             | 2000                     | CC-6     | 1350           | 24          |
| 50178                                                | 100G40/WH/2M/120V/STD BLX             | 100          | E26  | 120          | White             | 2000                     | CC-6     | 1200           | 12          |
| 50179                                                | 150G40/WH/2M/120V/STD BLX             | 150          | E26  | 120          | White             | 2000                     | CC-6     | 1650           | 12          |
| <b>R20</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)  |                                       |              |      |              |                   |                          |          |                |             |
| 51080                                                | 30R20/FL/2M/120V/STD BLX              | 30           | E26  | 120          | Frost             | 2000                     | CC-6     | 170            | 60          |
| 61706                                                | 45R20/FL/2M/120V/STD BLX              | 45           | E26  | 120          | Frost             | 2000                     | CC-6     | 380            | 60          |
| <sup>†</sup> 51081                                   | 75R20/FL/2M/120V/STD BLX              | 75           | E26  | 120          | Clear             | 2000                     | C-9/5    | 650            | 200         |
| <b>S11</b>                                           |                                       |              |      |              |                   |                          |          |                |             |
| MOL : 2 3/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)     |                                       |              |      |              |                   |                          |          |                |             |
| 52167                                                | 40S11/CL/1M/E17/120V/STD BLX          | 40           | E17  | 120          | Clear             | 1000                     | C-7A     | 400            | 500         |

<sup>†</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.