



MR11 (G4)



MR16 (GX5.3)



MR16 (E26)



MR16 (GU10)



Order code	Description	ANSI code	Watts (W)	Base	Volts (V)	Colour temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Average life (hrs)	Initial lumens (lm)	Case qty
------------	-------------	-----------	-----------	------	-----------	------------------	----------------	-------------	-----------	--------------------	---------------------	----------

MR11 - Cover Glass

MOL : 1 3/8 in. (35 mm) Dia. : 1 3/8 in. (35 mm)

55094	H10MR11/NSP/CG/2M/G4/6V/STD	N/A	10	G4	6	2 900	10	Narrow Spot	700	2 000	80	100
55054	H5MR11/NSP/CG/2M/G4/12V/STD	N/A	5	G4	12	2 900	10	Narrow Spot	700	2 000	45	120
50900	H20MR11/NFL/CG/2M/G4/12V/FTC STD	FTC/CG	20	G4	12	2 900	17	Narrow Flood	1 600	2 000	200	200
51050	H20MR11/MFL/CG/2M/G4/12V/FTD STD	FTD/CG	20	G4	12	2 900	27	Flood	600	2 000	200	120
50901	H35MR11/NFL/CG/2M/G4/12V/FTF STD	FTF/CG	35	G4	12	2 900	18	Narrow Flood	3 000	2 000	345	200
50899	H35MR11/MFL/CG/2M/G4/12V/FTH STD	FTH/CG	35	G4	12	2 900	28	Flood	1 300	2 000	345	120

MR11 - Open

MOL : 1 3/8 in. (35 mm) Dia. : 1 3/8 in. (35 mm)

50894	H20MR11/NSP/AX/G4/12V/FTB STD	FTB	20	G4	12	2 900	11	Narrow Spot	5 000	2 000	200	200
50895	H20MR11/NFL/AX/G4/12V/FTC STD	FTC	20	G4	12	2 900	19	Narrow Flood	1 600	2 000	200	120
51054	H20MR11/MFL/AX/G4/12V/FTD STD	FTD	20	G4	12	2 900	29	Flood	600	2 000	200	120
50897	H35MR11/NFL/AX/G4/12V/FTF STD	FTF	35	G4	12	2 900	19	Narrow Flood	3 000	2 000	345	200
50898	H35MR11/MFL/AX/G4/12V/FTH STD	FTH	35	G4	12	2 900	30	Flood	1 300	2 000	345	120

MR16 - Cover Glass

MOL : 1 25/32 in. (45 mm) Dia. : 2 in. (51 mm)

51134	H20MR16/FL/CG/4M/GX5.3/12V/BAB STD	BAB/CG	20	GX5.3	12	2 950	38	Flood	500	4 000	260	100
50892	H35MR16/FL/CG/4M/GX5.3/12V/FMW STD	FMW/CG	35	GX5.3	12	3 000	38	Flood	1 000	4 000	530	100
50893	H50MR16/FL/CG/4M/GX5.3/12V/EXN STD	EXN/CG	50	GX5.3	12	3 050	38	Flood	1 600	4 000	850	100

MR16 - Cover Glass - Line Voltage

MOL : 2 5/32 in. (55 mm) Dia. : 2 in. (51 mm)

55570*	H35MR16/FL/CG/2M/E26/120V/STD	N/A	35	E26	120	2 800	38	Flood	800	2 000	240	100
57312*	H50MR16/FL/CG/2M/E27/120V/STD	N/A	50	E27	120	2 800	30	Flood	1 100	2 000	420	200
55569*	H50MR16/FL/CG/2M/E26/120V/STD	N/A	50	E26	120	2 800	38	Flood	1 100	2 000	420	100
59590*	H35MR16/FL/CG/E26/130V/STD	N/A	35	E26	130	2 800	38	Flood	800	2 500	180	100
59589*	H50MR16/FL/CG/E26/130V/STD	N/A	50	E26	130	2 800	38	Flood	1 100	2 500	315	100

MR16 (GU10)

MOL : 2 5/32 in. (55 mm) Dia. : 2 in. (51 mm)

55034	H20GU10/NFL/CG/2.5M/120V/STD		20	GU10	120	2 800	25	Narrow Flood	500	2 500	120	100
55033	H35GU10/NFL/CG/2.5M/120V/STD		35	GU10	120	2 800	25	Narrow Flood	1 000	2 500	280	100
10437	H50GU10/NFL/CG/2.5M/120V/STD		50	GU10	120	2 800	25	Narrow Flood	1 400	2 500	500	100
55035	H50GU10/NFL/2M/CG/120V/ HS		50	GU10	120	2 800	25	Narrow Flood	1 400	2 000	N/A	15
10438	H50GU10/NFL/CG/3M/130V/STD		50	GU10	130	2 800	25	Narrow Flood	1 400	3 000	375	100

MR16 - Open

MOL : 1 25/32 in. (45 mm) Dia. : 2 in. (51 mm)

51066	H20MR16/FL/4M/GX5.3/12V/BAB STD	BAB	20	GX5.3	12	2 950	36	Flood	500	4 000	260	100
50888	H35MR16/FL/4M/GX5.3/12V/FMW STD	FMW	35	GX5.3	12	3 000	38	Flood	1 000	4 000	530	200
50889	H50MR16/NSP/4M/GX5.3/12V/EXT STD	EXT	50	GX5.3	12	3 050	13	Narrow Spot	9 800	4 000	850	100
50890	H50MR16/NFL/4M/GX5.3/12V/EXZ STD	EXZ	50	GX5.3	12	3 050	24	Narrow Flood	3 200	4 000	850	100
50891	H50MR16/FL/4M/GX5.3/12V/EXN STD	EXN	50	GX5.3	12	3 050	38	Flood	1 600	4 000	850	100



DIMMABLE



UV STOP

MR11 & MR16 Lamps