

Project:		Type:
		7F -
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LED TAPE KIT

EASY DIY

RGB

ORDERING INFORMATION

61953 Order code:

LED/TAPE/16.4'/5050/RGB KIT/12V/50M/STD Model number:

UPC: 069549619531

Case quantity:

PHYSICAL DATA

Reel Total Length: 16.4 ft. (5m) Number of LED: 30 LEDs per meter 9 LEDs per foot

4 in. (100 mm) or every 3 LED chips **Cuttable length: Operating Temperature:** -25°C to 60°C (-13°F to 140°F)

PERFORMANCE DATA

Watts (W): Volts (V DC): 12 RGB Color temperature (K)1: Life L70 (h)3: 30 000 Dimming: Yes4 **Environment:** Damp Beam angle (°): 115

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing, Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

⁴ Dimming is only available using the "Brightness +/-" option on the remote control.

Included in the box

1 Tape light 16.4' (5m)
1 Plug-in driver
1 RGB remote control (for RGB kit only)
1 RGB Controller
2 End caps

COMPATIBLE ACCESSORIES

Order code	Description	Туре
61956	LED/TAPE/RGB/CONNECTOR/STD	RGB Connector
61957	LED/TAPE/WW+CW/CONNECTOR/STD	Connector
62017	LED/10PCS TAPE LIGHT MOUNTING CLIPS	Mounting clips

This lighting equipment meets requirements of ICES-005 issue 5 class B for use in residential applications. Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.













LED TAPE KIT

DIMENSIONS

F																		
7.874" (200 mm)					196.85" (5 000 mm)									-				
—														<u>-</u> =	<u></u>			0.11" (2.8 mm)
619	953																	0.11 (2.0 min)
—											- /						ı	
						7]		
		4.06" (100 mm)	-		-	1.3	1" (33.3 mi	m)		-								0.394" (10.0 mm)

Qty	Description	Price	
	ations of the luminaire configuration mentioned above.		
Name: Company: Signature:			
Signature:		Date:	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Stanpro customer service representative to confirm inventory levels at time of order.

