


ORDERING INFORMATION

Order code: 63028
Description: E454T5HOPS347/N/XTRM
UPC: 69549630284



SPECIFICATIONS

Ballast type: Electronic
Starting method: Program Start
Lamp connection: Series
Input voltage (V): 347V
Input frequency (Hz): 60Hz
Max. case temperature: 90 °C
Thermal protection: Class P

Type: 1 Outdoor
Contains PCBs: No
Sound rating: A
Open current voltage (OCV) (V): 600
Inherent thermal protection: Yes
Lamp protection circuit: Yes
ICES-005 Compliant: Class A RFLD
End of life (EoL) protection: Yes
Auto-restrike: Yes



Lamp type	Number of lamps	Rated lamp watts	Min. start temp. (°F / °C)	Input current (A)	Input power (ANSI watts)	Ballast factor	Max THD (%)	Power factor	Max. lamp current crest factor	B.E.F.
347 VOLTS										
F54T5HO (54W)	4	54	-22/-30	0.67	230	0.98	10	0.98	1.7	0.43
F54T5HO/ES (49W)	4	49	-22/-30	0.62	212	0.98	10	0.98	1.7	0.46
PL55/TTL (55W)	4	55	-22/-30	0.58	198	0.88	10	0.98	1.7	0.44
PL50/TTL (50W)	4	50	-22/-30	0.65	224	1.08	10	0.98	1.7	0.48
F39T5HO (39W)	4	39	-22/-30	0.49	170	1.00	10	0.98	1.7	0.59
F54T5HO (54W)	3	54	-22/-30	0.51	176	1.00	10	0.98	1.7	0.57
F54T5HO/ES (49W)	3	49	-22/-30	0.50	169	1.00	10	0.98	1.7	0.59
PL55/TTL (55W)	3	55	-22/-30	0.45	153	0.90	10	0.98	1.7	0.59
PL50/TTL (50W)	3	50	-22/-30	0.49	169	1.08	10	0.98	1.7	0.64
F54T5HO (54W)	2	54	-22/-30	0.34	118	0.99	15	0.97	1.7	0.84
F54T5HO/ES (49W)	2	49	-22/-30	0.33	113	0.99	15	0.97	1.7	0.88
PL55/TTL (55W)	2	55	-22/-30	0.29	102	0.92	15	0.97	1.7	0.90
PL50/TTL (50W)	2	50	-22/-30	0.30	103	1.10	15	0.97	1.7	1.07
F54T5HO (54W)	1	54	-22/-30	0.17	60	1.02	15	0.97	1.7	1.70
F54T5HO/ES (49W)	1	49	-22/-30	0.17	58	1.02	15	0.97	1.7	1.76
PL55/TTL (55W)	1	55	-22/-30	0.16	56	0.95	15	0.97	1.7	1.70
PL50/TTL (50W)	1	50	-22/-30	0.16	55	1.10	15	0.97	1.7	2.00

WARRANTY:




Ballast warranty of 5 years for electronic ballast 75 °C. Ballast warranty of 3 years for electronic ballast 90 °C.
For more information visit our website.

Data is based upon tests performed in a controlled environment and representative of relative performance.
Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.
March 9, 2015

ORDERING INFORMATION

Order code: 63028
 Description: E454T5HOPS347/N/XTRM
 UPC: 69549630284

WIRING DIAGRAM




LEADS LENGTH

Black	18" (45.72 cm)
White	18" (45.72 cm)
Blue	30" (76.20 cm)
Red	30" (76.20 cm)
Yellow	30" (76.20 cm)
Grey	22" (55.88 cm)
Blue/White	48" (121.92 cm)
Brown	40" (101.6 cm)
Orange	56" (142.24 cm)

BALLAST DIMENSIONS

Length (L):	17.71" (45.0 cm)
Width (W):	1.70" (4.30 cm)
Height (H):	1.14" (2.90 cm)
Mounting (M):	17.24" (43.8 cm)



WARRANTY:

Ballast warranty of 5 years for electronic ballast 75 °C. Ballast warranty of 3 years for electronic ballast 90 °C.
 For more information visit our website.

Data is based upon tests performed in a controlled environment and representative of relative performance.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.
 March 9, 2015