



Ambiance

Choose from clear and frost

Style and Savings

Spend less with a cost of \$0.42 per year on energy and maintenance

Long Life

Lasts 8 times longer than an incandescent lamp

Decorative

Many shapes to choose from

Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs. Completely dimmable, these incandescent replacements allow the user to create a comfortable atmosphere for any occasion while generating less heat.

They are perfect for use in chandeliers, wall sconces and ornamental fixtures.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	Average life L70 ¹ (hrs)	Initial lumens ² (lm)	Traditional equivalent (W)	Dimmable ³ (Y/N)	Case qty (inner/master)
A15											
MOL : 3 1/2 in. (82 mm) Dia. : 1 9/16 in. (45 mm)											
63745	LED/A15/5W/27K/STD	5	E26	120	2 700	Clear	25 000	300	40	Y	6/48
63744	LED/A15/5W/27K/F/STD	5	E26	120	2 700	Frost	25 000	300	40	Y	6/48
63731	LED/A15/5W/40K/F/STD	5	E26	120	4 000	Frost	25 000	300	40	Y	6/48
MOL : 3 15/32 in. (88 mm) Dia. : 1 7/8 in. (48 mm)											
63733	LED/A15/7W/27K/STD	7	E26	120	2 700	Clear	25 000	450	40	Y	6/48
63734	LED/A15/7W/27K/F/STD	7	E26	120	2 700	Frost	25 000	507	40	Y	6/48
63735	LED/A15/7W/30K/F/STD	7	E26	120	3 000	Frost	25 000	514	40	Y	6/48
63732	LED/A15/7W/40K/F/STD	7	E26	120	4 000	Frost	25 000	505	40	Y	6/48
B11											
MOL : 4 1/16 in. (103 mm) Dia. : 1 3/8 in. (35 mm)											
63137	LED/B11/4.7W/27K/E12/STD	4.7	E12	120	2 700	Clear	40 000	330	40	Y	24/48
B13											
MOL : 4 1/8 in. (105 mm) Dia. : 1 3/8 in. (35 mm)											
63138	LED/B13/7W/27K/E12/STD	7	E12	120	2 700	Clear	40 000	500	60	Y	24/48
C12											
MOL : 3 13/16 in. (97 mm) Dia. : 1 13/32 in. (36 mm)											
63742	LED/C12/3W/27K/STD	3	E26	120	2 700	Clear	25 000	200	25	Y	6/48
63741	LED/C12/3W/27K/E12/STD	3	E12	120	2 700	Clear	25 000	200	25	Y	6/48
63739	LED/C12/3W/27K/F/E12/STD	3	E12	120	2 700	Frost	25 000	200	25	Y	6/48
63743	LED/C12/5W/27K/STD	5	E26	120	2 700	Clear	25 000	316	40	Y	6/48
63740	LED/C12/5W/27K/F/E12/STD	5	E12	120	2 700	Frost	25 000	338	40	Y	6/48
G16.5											
MOL : 2 9/16 in. (74 mm) Dia. : 1 15/16 in. (49 mm)											
63736	LED/G16.5/3W/27K/E12/STD	3	E12	120	2 700	Clear	25 000	200	25	Y	6/48
63737	LED/G16.5/5W/27K/E12/STD	5	E12	120	2 700	Clear	25 000	375	40	Y	6/48
63738	LED/G16.5/5W/27K/E12/F/STD	5	E12	120	2 700	Frost	25 000	375	40	Y	6/48
G25											
MOL : 4 1/4 in. (108 mm) Dia. : 3 5/32 in. (80 mm)											
63622	LED/G25/6W/30K/F/STD	6	E26	120	3 000	Frost	25 000	470	30	Y	6/24



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 10 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com

Small and efficient

G4 and G9 lamps offer bright and crisp white light in a very compact profile. There is no UV or IR radiation in the light beam. These lamps are completely certified line voltage G9 lamps.

These lamps are ideal for task lighting, under cabinet lighting display cases, pendant lighting and accent lighting throughout homes, museums, hotels and restaurants.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	Average life L70 (hrs)	Initial lumens ¹ (lm)	Beam angle (°)	Traditional equivalent (W)	Dimmable ² (Y/N)	Case qty (inner/master)
------------	-------------	-----------	------	-------------	------------------	--------	------------------------	----------------------------------	----------------	----------------------------	-----------------------------	-------------------------

JC-G4

MOL: 1 5/8 in. (41 mm) Dia.: 5/8 in. (16 mm)

62805*	LED/G4/2.5W/30K/12V/ND/STD	2.5	G4	12	3 000	Clear	15 000	200	120	18	N	10/100
--------	----------------------------	-----	----	----	-------	-------	--------	-----	-----	----	---	--------

JD-G9

MOL: 1 7/8 in. (48 mm) Dia.: 5/8 in. (16 mm)

63618	LED/G9/2.5W/27K/STD	2.5	G9	120	2 700	Frost	20 000	190	300	18	Y	50/200
63619	LED/G9/2.5W/30K/STD	2.5	G9	120	3 000	Frost	20 000	200	300	18	Y	50/200
63620	LED/G9/2.5W/40K/STD	2.5	G9	120	4 000	Frost	20 000	210	300	18	Y	50/200
63444**	LED/G9/3.5W/27K/STD	3.5	G9	120	2 700	Frost	30 000	210	300	18	Y	50/500
63445**	LED/G9/3.5W/30K/STD	3.5	G9	120	3 000	Frost	30 000	225	300	18	Y	50/500
63446**	LED/G9/3.5W/40K/STD	3.5	G9	120	4 000	Frost	30 000	245	300	18	Y	50/500
64428	LED/G9/HO/3.5W/27K/F/STD	3.5	G9	120	2 700	Frost	10 000	330	330	30	Y	50/200
64427	LED/G9/HO/3.5W/30K/STD	3.5	G9	120	3 000	Clear	10 000	390	330	30	Y	50/200
64429	LED/G9/HO/3.5W/30K/F/STD	3.5	G9	120	3 000	Frost	10 000	360	330	30	Y	50/200
64430	LED/G9/HO/3.5W/40K/F/STD	3.5	G9	120	4 000	Frost	10 000	390	330	30	Y	50/200
64849	LED/G9/HO/3.5W/50K/STD	3.5	G9	120	5 000	Clear	10 000	410	330	30	Y	50/200

R7S

Step away from halogen technology with these LED double-ended tubes. They are ideal for everyday use in residential applications for torchiere lamps, bath bar vanity fixtures and wall sconces.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	Finish	Average life L70 (hrs)	Initial lumens ¹ (lm)	Beam angle (°)	Traditional equivalent (W)	Dimmable ² (Y/N)	Case qty (inner/master)
------------	-------------	-----------	------	-------------	------------------	--------	------------------------	----------------------------------	----------------	----------------------------	-----------------------------	-------------------------

R7S

Dia.: 29/32 in. (23 mm)

64466*	LED/R7S/5W/30K/78/ND/STD	5	R7S	120	3 000	Clear	15 000	450	360	50	N	50/200
64467*	LED/R7S/8W/30K/118/ND/STD	8	R7S	120	3 000	Clear	15 000	650	360	100	N	50/200



¹ Typical lumens +/- 10 %

² For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com

Decoratives

R7S



G9



Omni

