

Date: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_  
 Name of distributor: \_\_\_\_\_  
 Client #: \_\_\_\_\_  
 Name of end user: \_\_\_\_\_

## ORDERING INFORMATION

Order code: 65048  
 Description: LED/CRN/54W/40K/ND/BYP/E39/120-277/STD  
 UPC: 69549650480  
 Case quantity: 12

## PERFORMANCE DATA

Base: E39  
 Wattage (W): 54  
 Lamp voltage (VAC): 120-277  
 Colour temperature (K)\*\*: 4 000  
 Average life (L70 hours): 50 000  
 Initial lumens (lm)\*: 7 020  
 Initial lumens per watt (lm/W): 130  
 CRI: 80  
 Beam angle (°): 360  
 Power factor: 0.9  
 Operating temperature range: -20 °C / - 4 °F to 45 °C / 113 °F

\*Initial lumens range: +/- 10 %

\*\*Typical colour temperature range: +/- 5 %



DAMP



NO  
MERCURY



WARRANTY



COMPLIANT



UL US



FC

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

## CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock – do not use where directly exposed to water or weather.
- Suitable for use in totally enclosed luminaires, however ensure that there is adequate space around the device for heat dissipation.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Added weight of the device may cause instability of a freestanding portable luminaire.
- Use only on 120-277 VAC, 50/60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Not for use with dimmers.
- For complete warranty information visit [www.standardpro.com](http://www.standardpro.com)



MOL: 10 7/16 in. (265 mm) Dia.: 3 15/32 in. (91 mm)

## TRADITIONAL EQUIVALENT

| CFL      | Incandescent | HID  |
|----------|--------------|------|
| 85W/105W | 500W         | 250W |

| Qty | Description | Price |
|-----|-------------|-------|
|     |             |       |

I accept the specifications of the lamp configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Data is based upon tests performed in a controlled environment and representative of relative performance.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

October 20, 2016

**STANDARD**<sup>®</sup>