



LED General Purpose

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.

From Omni lamps to small halogen replacements, these lamps deliver a brighter look and provide the same even, crisp and comfortable lighting as traditional lamps. A wide selection of color temperatures is offered to obtain the desired lighting effect and can be adapted to all applications.



Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
A19 40 W equivalent												
69676	A19/S6/6W/27K/STD	6	E26	120	2 700	Frost	80	25 000	480	40	Yes	1/50
69677	A19/S6/6W/30K/STD	6	E26	120	3 000	Frost	80	25 000	480	40	Yes	1/50
69678	A19/S6/6W/40K/STD	6	E26	120	4 000	Frost	80	25 000	480	40	Yes	1/50
67951	LED/A19/S5/6W/50K/STD	6	E26	120	5 000	Frost	80	25 000	480	40	Yes	1/100
60 W equivalent												
69680	A19/S6/8W/27K/STD	8	E26	120	2 700	Frost	80	25 000	800	60	Yes	1/50
69681	A19/S6/8W/30K/STD	8	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/50
69682	A19/S6/8W/40K/STD	8	E26	120	4 000	Frost	80	25 000	800	60	Yes	1/50
69683	A19/S6/8W/50K/STD	8	E26	120	5 000	Frost	80	25 000	800	60	Yes	1/50
60 W equivalent - 4 pack												
69692	A19/S6/8W/27K/STD 4P	8	E26	120	2 700	Frost	80	25 000	800	60	Yes	4/48
68002	LED/A19/S2/9W/30K/STD 4P	9	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/96
69694	A19/S6/8W/40K/STD 4P	8	E26	120	4 000	Frost	80	25 000	800	60	Yes	4/48
69695	A19/S6/8W/50K/STD 4P	8	E26	120	5 000	Frost	80	25 000	800	60	Yes	4/48
60 W equivalent - GU24												
69841	A19/S2/8W/27K/GU24/STD	8	GU24	120	2 700	Frost	80	25 000	800	60	Yes	1/50
69842	A19/S2/8W/30K/GU24/STD	8	GU24	120	3 000	Frost	80	25 000	800	60	Yes	1/50
66277	A19/9.8W/40K/GU24/PRO/STD	9.8	GU24	120	4 000	Frost	86	25 000	868	60	Yes	6/48
75 W equivalent												
67956	LED/A19/S5/12W/27K/STD	12	E26	120	2 700	Frost	80	25 000	1 100	75	Yes	1/100
69685	A19/S6/11W/30K/STD	11	E26	120	3 000	Frost	80	25 000	1 100	75	Yes	1/50
67958	LED/A19/S5/12W/40K/STD	12	E26	120	4 000	Frost	80	25 000	1 100	75	Yes	1/100
67959	LED/A19/S5/12W/50K/STD	12	E26	120	5 000	Frost	80	25 000	1 100	75	Yes	1/100
100 W equivalent												
69688	A19/S6/13W/27K/STD	13	E26	125	2 700	Frost	80	25 000	1 600	100	Yes	1/50
69689	A19/S6/13W/30K/STD	13	E26	125	3 000	Frost	80	25 000	1 600	100	Yes	1/50
69690	A19/S6/13W/40K/STD	13	E26	125	4 000	Frost	80	25 000	1 600	100	Yes	1/50
69691	A19/S6/13W/50K/STD	13	E26	120	5 000	Frost	80	25 000	1 600	100	Yes	1/50

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



Trilight

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
Trilight												
65613	LED/A19/S2/12W/27K/3WAY/STD	3/9/12	E26	120	2 700	Frost	81	25 000	280/950/1 200	30/70/100	No	6/24
65614	LED/A19/S2/12W/30K/3WAY/STD	3/9/12	E26	120	3 000	Frost	83	25 000	280/950/1 200	30/70/100	No	6/24

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com





Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Case qty (inner/master)
A15										
66758	A15/S2/6W/27K/CL/STD	6	E26	120	2 700	Clear	15 000	514	60	24/48
66759	A15/S2/5.5W/27K/FR/STD	5.5	E26	120	2 700	Frost	15 000	496	60	24/48
66760	A15/S2/6W/30K/CL/STD	6	E26	120	3 000	Clear	15 000	592	60	24/48
66761	A15/S2/5.5W/30K/FR/STD	5.5	E26	120	3 000	Frost	15 000	511	60	24/48
66762	A15/S2/5.5W/40K/FR/STD	5.5	E26	120	4 000	Frost	15 000	530	60	24/48
C12										
66763	C12/S2/4.5W/27K/CL/STD	4.5	E26	120	2 700	Clear	15 000	322	40	24/48
66764	C12/S2/4.5W/27K/E12/CL/STD	4.5	E12	120	2 700	Clear	15 000	322	60	24/48
66765	C12/S2/4.5W/27K/E12/FR/STD	4.5	E12	120	2 700	Frost	15 000	331	60	24/48
G16.5										
66766	G16.5/S2/5W/27K/E12/CL/STD	5	E12	120	2 700	Clear	15 000	365	60	24/48
66767	G16.5/S2/5W/27K/E12/FR/STD	5	E12	120	2 700	Frost	15 000	361	60	24/48
G25										
66768	G25/S2/7W/27K/FR/STD	7	E26	120	2 700	Frost	15 000	553	60	24/48
66769	G25/S2/7W/30K/FR/STD	7	E26	120	3 000	Frost	15 000	553	60	24/48

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com