Technical Information Bulletin



Worklights

Date:	Name of distributor:	Name of distributor:				
In hands date of project:	Client #:					
Project name/Number:	Name of end user:					

ORDERING INFORMATION

Order code: 67022

Description: PFL/BTRY/100-240/50W/CW/YL/STD

UPC: 69549670228

Case quantity: 2

PHYSICAL DATA

Type: LED Flood Light

Housing colour: Yellow
Housing Material: Aluminium

PERFORMANCE DATA

Watts (W): 50 Volts (VAC): 100-240 Cool White Colour temp.: 3 250 Lumen output (lm)1: Lumen per Watts (Im/W): 65 70 CRI: at 20% Brightness 12 **Battery** at 50% Brightness 6 working time (h): at 100% Brightness 3 Battery Charging time (h) 6 Beam angle (°): 120

Amperage (A): 6.6
Battery Specifications: 18.5V 6.6AH

Environment: Dry

Operating temp. range: -10°C to 40°C (14°F to 104°F)

Dimming: Yes

 $^{\rm l}$ Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %














TECHNICAL DRAWINGS AND DIMENSIONS



COMPATIBLE ACCESSORIES

Order code	Description	Туре				
67025	PFL/TRIPOD/YL/STD	Tripod				
67027	PEL/CHARGER/50W/STD	50 W replacement battery charger				

DESCRIPTION AND OTHER OPTIONS

	PLF	/	В	BTRY	/	100	0-240	/	50)W	/		CW	/	YL		/		STD
	Family		Fe	eature		Vo	olts (V)		Watt	s (W)		Colour Temperature Colour		r			Brand		
PLF	Portable Flood Light		BTRY	Battery Powered		100-240	100-240 Volts		50W 20W	50 Watts 20 Watts		cw	Cool White		YL	Yellow		STD	STANDARD

Qty	Description	Price	
I accept the spe	cifications of the luminaire configuration mentioned above.		
Name:			
Company:			
Signature:		Date:	
Name: Company:	cifications of the luminaire configuration mentioned above.		