Technical Information Bulletin LED Lamps



Date:	Name of distributor:
In hands date of project:	Client #:
Project name/Number:	Name of end user:

ORDERING INFORMATION

Order code: 67953 LED/A19/S5/9W/30K/STD Description: UPC: 069549679535 1 / 100 Case quantity:



PERFORMANCE DATA

A19
9
E26
120
3 000
25 000
800
89
80
220
0.70
- 30 °C / - 22 °F to 40 °C / 104 °F

*Initial lumens range: +/- 10 % **Typical colour temperature range: +/- 5 %





CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock do not use where directly exposed to water or weather.
- · Suitable for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- · For complete dimmer and warranty information visit www.standardpro.com.

Qty	Description	Price
I accept the spe	ecifications of the luminaire configuration menti	oned above.
Name:		
Company:		
Signature:		Date:

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

COMPATIBLE DIMMERS

Brand	Model
Lutron	PD-5NE, RRD-6NA, DVCL-153P, CTCL-153P, AYCL-253P, DVRP-253, SELV-300P
Legrand	RH703PTUTC
Leviton	DDMX1

Dimming performance might be impacted when using the above dimmers with only one lamp Full performance achieved with at two or more lamps.