



LED Reflector

Allowing you to focus light where it matters, these LED reflectors will not let your colors fade. Choose from many sizes, color temperatures and beam distributions to create the perfect lighting with consistent lamp to lamp color.

Reduce energy consumption and protect all goods and materials that are sensitive to heat and UV emissions.

STANDARD's LED reflectors are ideal for tracks, recessed luminaires and accent lighting in residential, retail, hospitality and commercial applications.



MR11



MR16



GU10



GU10
5 CCT 25°



GU10
5 CCT 40°

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (master)
MR11												
64244	LED/MR11/4W/30K/38/GU4/ND/STD	4	GU4	12	3 000	80	25 000	260	38	550	30	48
MR16												
68263	MR16/S2/7.5W/27K/25/STD	7.5	MR16	12	2 700	90	54 000	570	25	3 196	75	60
68259	MR16/S2/7.5W/27K/35/STD	7.5	GU5.3	12	2 700	90	50 000	570	35	1 908	75	60
68264	MR16/S2/7.5W/30K/25/STD	7.5	GU5.3	12	3 000	90	54 000	570	25	3 268	50	60
68260	MR16/S2/7.5W/30K/35/STD	7.5	GU5.3	12	3 000	90	50 000	570	35	1 905	75	60
68265	MR16/S2/7.5W/40K/25/STD	7.5	GU5.3	12	4 000	90	50 000	570	25	3 613	75	60
68261	MR16/S2/7.5W/40K/35/STD	7.5	GU5.3	12	4 000	90	50 000	570	35	2 066	75	60
68262	MR16/S2/7.5W/50K/35/STD	7.5	GU5.3	12	5 000	90	54 000	570	35	2 020	50	60
GU10 CCT Selectable												
69729	GU10/6.5W/5CCT/25/STD	6.5	GU10	120	2 700/3 000/3 500/4 000/5 000	80	25 000	500	25	-	50	100
69626	GU10/6.5W/5CCT/40/STD	6.5	GU10	120	2 700/3 000/3 500/4 000/5 000	80	25 000	500	40	502	50	100
GU10												
68252	GU10/S2/6.5W/27K/25/STD	6.5	GU10	120	2 700	90	54 000	570	25	1 975	75	60
68255	GU10/S2/6.5W/27K/35/STD	6.5	GU10	120	2 700	90	54 000	570	35	1 231	75	60
68253	GU10/S2/6.5W/30K/25/STD	6.5	GU10	120	3 000	90	54 000	570	25	1 975	75	60
68256	GU10/S2/6.5W/30K/35/STD	6.5	GU10	120	3 000	90	54 000	570	35	1 996	50	60
68257	GU10/S2/6.5W/40K/35/STD	6.5	GU10	120	4 000	90	54 000	570	35	1 231	50	60

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



PAR20
5 CCT



PAR30SN
5 CCT



PAR20



PAR30SN

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (master)
------------	-------------	-----------	------	-------------	-----------------	-----	----------------	-------------------	----------------	-----------	----------------------------	-------------------

PAR20 CCT SELECTABLE

69641 ^{2,3}	P20/6.5W/5CCT/25/STD	6.5	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	540	25	1 800	50	24
69642 ^{2,3}	P20/6.5W/5CCT/40/STD	6.5	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	540	40	1 100	50	24

PAR20

68218	P20/S2/7W/27K/25/STD	7	E26	120	2 700	90	54 000	550	25	3 422	50	12
68219	P20/S2/7W/27K/40/STD	7	E26	120	2 700	92	54 000	550	40	1253	50	12
68220	P20/S2/7W/30K/25/STD	7	E26	120	3 000	90	54 000	550	25	3 572	50	12
68221	P20/S2/7W/30K/40/STD	7	E26	120	3 000	90	54 000	550	40	1 303	50	12
68222	P20/S2/7W/40K/25/STD	7	E26	120	4 000	90	54 000	550	25	3 829	50	12
68224	P20/S2/7W/40K/40/STD	7	E26	120	4 000	90	54 000	550	40	1 358	50	12
68225	P20/S2/7W/50K/25/STD	7	E26	120	5 000	90	54 000	550	25	2 350	50	12
68226	P20/S2/7W/50K/40/STD	7	E26	120	5 000	90	54 000	550	40	1 257	50	12

PAR30SN CCT SELECTABLE

69643 ^{2,3}	P30S/11W/5CCT/25/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	25	3 200	75	24
69644 ^{2,3}	P30S/11W/5CCT/40/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	40	1 800	75	24

PAR30SN

68227	P30S/S2/12W/27K/25/STD	12	E26	120	2 700	90	54 000	1 050	25	4 981	75	6
68228	P30S/S2/12W/27K/40/STD	12	E26	120	2 700	90	54 000	1 050	40	2 337	75	6
68229	P30S/S2/12W/30K/25/STD	12	E26	120	3 000	90	54 000	1 050	25	5 435	75	6
68230	P30S/S2/12W/30K/40/STD	12	E26	120	3 000	90	54 000	1 050	40	2 470	75	6
68232	P30S/S2/12W/40K/40/STD	12	E26	120	4 000	90	54 000	1 050	40	2 711	75	6
68233	P30S/S2/12W/50K/25/STD	12	E26	120	5 000	90	54 000	1 050	25	4 450	75	6

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com
¹ Not Energy Star

6³

wet
location

6

damp
location



dimable

3²
yrs
warranty

5²
yrs
warranty





PAR30LN
5 CCT



PAR38
5 CCT



PAR38
5 CCT



PAR30LN



PAR38

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (inner/master)
------------	-------------	--------------	------	----------------	--------------------	-----	----------------------	----------------------	-------------------	--------------	-------------------------------	----------------------------

PAR30LN CCT SELECTABLE

69645 ^{2,3}	P30L/11W/5CCT/25/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	25	3 200	75	6/24
69646 ^{2,3}	P30L/11W/5CCT/40/STD	11	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	900	40	1 800	75	6/24

PAR30LN

68235	P30L/S2/12W/27K/25/STD	12	E26	120	2 700	90	50 000	1 050	25	5 240	75	6
68236	P30L/S2/12W/27K/40/STD	12	E26	120	2 700	90	54 000	1 050	40	2 117	75	6
68237	P30L/S2/12W/30K/25/STD	12	E26	120	3 000	90	54 000	1 050	25	5 137	75	6
68239	P30L/S2/12W/40K/25/STD	12	E26	120	4 000	90	54 000	1 050	25	5 359	75	6
68240	P30L/S2/12W/40K/40/STD	12	E26	120	4 000	90	54 000	1 050	40	2 767	75	6
68241	P30L/S2/12W/50K/25/STD	12	E26	120	5 000	90	54 000	1 050	25	5 473	75	6
68242	P30L/S2/12W/50K/40/STD	12	E26	120	5 000	90	54 000	1 050	40	2 471	75	6

PAR38 CCT SELECTABLE

69647 ^{2,3}	P38/14W/5CCT/25/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	25	3 900	100	6/24
69648 ^{2,3}	P38/14W/5CCT/40/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	40	2 500	100	6/24
69654 ^{2,3}	P38/14W/5CCT/25/BK/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	25	3 900	100	6/24
69655 ^{2,3}	P38/14W/5CCT/40/BK/STD	14	E26	120	2 700/3 000/3 500/4 000/5 000	90	25 000	1 200	40	2 500	100	6/24

PAR38

68243	P38/S2/16.5W/27K/25/STD	16.5	E26	120	2 700	90	54 000	1 370	25	7 056	100	6
68244	P38/S2/16.5W/27K/40/STD	16.5	E26	120	2 700	90	50 000	1 370	40	2 783	120	6
68245	P38/S2/16.5W/30K/25/STD	16.5	E26	120	3 000	90	50 000	1 370	25	7 354	120	6
68246	P38/S2/16.5W/30K/40/STD	16.5	E26	120	3 000	90	50 000	1 370	40	3 127	120	6
68247	P38/S2/16.5W/40K/25/STD	16.5	E26	120	4 000	90	50 000	1 370	25	6 800	120	6
68250	P38/S2/16.5W/50K/25/STD	16.5	E26	120	5 000	90	54 000	1 370	25	6 800	120	6
68251	P38/S2/16.5W/50K/40/STD	16.5	E26	120	5 000	90	50 000	1 370	40	2 842	120	6

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com





PAR38
COLOR SELECTABLE LAMP

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (inner/master)
PAR38 Color Selectable												
69760	PAR38/8W/COLORSELECT/40/ND/STD	8	E26	120	6 color selectable-red,blue,green, yellow, orange, white (5 000K)	80	15 000	700	40	-	65	12

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products,
please visit www.standardpro.com


non
dimmable


wet
location


enclosed
fixture


2
yrs
warranty


UL
CERTIFIED


FCC



Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Case qty (inner/master)
R20 CCT Selectable												
69373 ^{2,3}	R20/6.5W/5CCT/STD	6.5	E26	120	2 700/3 000/3 500/4 000/5 000	80	25 000	615	105	180	50	6/24
BR30 CCT Selectable												
69374 ^{2,3}	BR30/8W/5CCT/STD	8	E26	120	2 700/3 000/3 500/4 000/5 000	80	25 000	735	105	235	75	6/24
BR40 CCT Selectable												
69375 ^{2,3}	BR40/12.5W/5CCT/STD	12.5	E26	120	2 700/3 000/3 500/4 000/5 000	80	25 000	1 180	105	390	100	6/24

Lumen values are derived from photometric testing
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com

