

Project:		Type:	
Drawn by:	Catalogue #:	Date:	

### Individual Spec Sheet

# **LED HIGH OUTPUT LAMP**

## A21

### **ORDERING INFORMATION**

69004 Order code:

Model number: A21H0/20W/40K/120-277/ND/STD

069549023284

Case quantity:

#### **PHYSICAL DATA**

A21 Shape: E26 Base: White Heat sink color: Finish: Frosted

#### **PERFORMANCE DATA**

Watts (W): 20 Traditional equivalent (W): 150 Volts (VAC): 120-277 Color temperature (K)1: 4 000 Lumen output (Im)2: 2 600 Efficacy (Im/W): 130 CRI: 80 Life L70 (h)3: 25 000 Beam angle (°): 220 Power factor (%): 0.90 Frequency (Hz): 50/60

Operating temp. range: - 30 °C to 40 °C (- 22 °F to 104 °F)







dimmable















This lighting equipment meets requirements of ICES-005 issue class B for use in residential applications. Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice

LED HIGH INTENSITY LAMP • Rev. 21/1/2022






<sup>&</sup>lt;sup>1</sup> Typical colour temperature range: +/- 5 %

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

<sup>3</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations



#### **DIMENSIONS**



Qty	Description	Price	
I accept the specification	ations of the luminaire configuration mentioned above.		
Name:			
Company: Signature:			
Signature:		Date:	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

