Product data sheet Characteristics

70-BSMLG-24

Protection module with LED indicator, SE Relays, for 782H hermetically sealed relays, green, 24VAC/VDC





Main

Product Range	Harmony Electromechanical Relays
Product Type	Protection module
Product Compatibility	Socket 70-781 plug-in Socket 70-782 plug-in

Complementary

[Ue] rated operational voltage	24 V	
Local Signalling	For coil powered 1 LED (green)	
Width	0.49 in (12.45 mm)	
Depth	0.34 in (8.64 mm)	

Ordering and shipping details

Category	21127-ZELIO ICE CUBE RELAYS
Discount Schedule	CP2
GTIN	3606480278327
Returnability	No
Country of origin	CN


Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	0.50 in (1.27 cm)	
Package 1 Width	0.70 in (1.78 cm)	
Package 1 Length	1.30 in (3.3 cm)	
Package 1 Weight	0.06 oz (1.7 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	1000	
Package 2 Height	5.31 in (13.5 cm)	
Package 2 Width	6.69 in (17 cm)	
Package 2 Length	10.43 in (26.5 cm)	
Package 2 Weight	8.82 lb(US) (4 kg)	
Package 3 Height	5.31 in (13.5 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Wiring Diagram



(1): MOV Suppressor(2): Protection Diode(3): LED Indicator(4): RC Suppressor