METAL BEND SUPPORT

>> 550-M SERIES

SPECIFICATION

Sioux Chief's 550-M Series metal bend support shall be used where necessary to provide support for bend radius on PEX tube without kinking the tube. Metal bend support shall be free from any burrs or rough edges and shall have a zinc-plated finish.

Sidewinder™

INSTALLATION

Carefully install tube into one open end of elbow then bend tube around and capture in opposite end of elbow. Do not kink tube.

MATERIALS

Zinc-plated CRS

DIMENSIONS

	550-M1	550-M2	550-M3
A: Material thickness	22 ga.	19 ga.	16 ga.
B: Overall length	3.07"	3.20"	5.02"
C: Bend radius	1.80"	2.11"	3.74"
D: 0.D. (outside diameter)	0.64"	0.77"	1.00"

ITEM # SUBMITTED	
JOB NAME	
LOCATION	
ENGINEER	
CONTRACTOR	
PO#	TAG





Create Item Number

550-MA

e.g. 550-M2: Metal bend support for 1/2" PEX.

SIZE A

- $\mathbf{1} = \frac{3}{8}$ " PEX bend support
- $\mathbf{2} = \frac{1}{2}$ " PEX bend support
- $\mathbf{3} = \frac{3}{4}$ " PEX bend support

