



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Combination ARC-fault
Ratings	HACR rated
Electrical Connection	Pressure plate
Connections Terminals	Pigtail neutral

Complementary

Interrupt Rating	10 kA 120 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	4.8 in (121 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net Weight	0.500 lb(US) (0.227 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A06303
Discount Schedule	DE2A
GTIN	785901438359
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.03 in (33.1 cm)
Package 1 Width	3.9 in (10 cm)
Package 1 Length	5.5 in (14 cm)
Package 1 Weight	9.0 oz (254 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	38
Package 2 Height	3.600 in (9.144 cm)
Package 2 Width	13.800 in (35.052 cm)

Package 2 Length	20.800 in (52.832 cm)
Package 2 Weight	21.499 lb(US) (9.752 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	2280
Package 3 Height	45.50 in (115.57 cm)
Package 3 Width	40.0000000000 in (101.6 cm)
Package 3 Length	42.0000000000 in (106.68 cm)
Package 3 Weight	1310.001 lb(US) (594.206 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------