



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Tandem
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 kA 120/240 V AC
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	35.4 lbf.in (4 N.m)
Height	3.2 in (82 mm)
Width	0.7 in (19 mm)
Depth	2.9 in (74 mm)
Net Weight	0.280 lb(US) (0.127 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00181
Discount Schedule	DE2A
GTIN	785901400905
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.79 in (7.08 cm)
Package 1 Width	0.43 in (1.08 cm)
Package 1 Length	3.16 in (8.02 cm)
Package 1 Weight	5.12 oz (145.15 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.56 in (9.05 cm)
Package 2 Width	3.57 in (9.08 cm)
Package 2 Length	7.49 in (19.03 cm)

Package 2 Weight	3.371 lb(US) (1.529 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	7.9 in (20.0 cm)
Package 3 Width	7.9 in (20.0 cm)
Package 3 Length	19.3 in (49.0 cm)
Package 3 Weight	34.410 lb(US) (15.608 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------