# QO240GFI

Mini circuit breaker, QO, 40A, 2 pole, 120/240VAC, 10kA, plug in, 6mA grd fault A, pigtail





#### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	40 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	Not rated
Electrical Connection	Box lugs

## Complementary

Interrupt Rating	10 KA 120/240 V AC 10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 12AWG 4 aluminium AWG 14AWG 6 copper	
Tightening Torque	44.3 Lbf.In (5 N.m) 40.7 lbf.in (4.6 N.m) 0.0060.03 in² (420 mm²) (AWG 12AWG 4)	
Height	4.1 in (105 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	1.030 lb(US) (0.467 kg)	

### Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

### Ordering and shipping details

Category	US1DE2A00103	
Discount Schedule	DE2A	
GTIN	785901764854	
Returnability	Yes	
Country of origin	US	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.50 in (8.89 cm)	
Package 1 Width	2.30 in (5.84 cm)	
Package 1 Length	5.30 in (13.46 cm)	
Package 1 Weight	16.48 oz (467.21 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	33	

Package 2 Height	5.50 in (13.97 cm)
Package 2 Width	13.700 in (34.798 cm)
Package 2 Length	21.200 in (53.848 cm)
Package 2 Weight	34.500 lb(US) (15.649 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

## Contractual warranty

Warranty	18 months