



# Mini circuit breaker, QO, 40A, 2 pole, 120/240VAC, 10kA, plug in

QO240

Product availability: Stock - Normally stocked in distribution

### Main

Product	Miniature circuit-breaker	
Range	QO	
Current Rating	40 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Plug-in	
Number of Poles	2P	
Circuit Breaker Type	Standard	
Ratings	HACR rated	
Electrical Connection	Box lugs	

## Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 8AWG 2 copper or aluminium	
Tightening Torque	44.3 lbf.in (5 N.m)	
Height	3.1 in (79 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.500 lb(US) (0.227 kg)	

#### **Environment**

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

## Ordering and shipping details

Category	US1DE2A00004	
Discount Schedule	DE2A	
GTIN	785901400486	
Returnability	Yes	
Country of origin	MX	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

# **Packing Units**

_		
Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	3.30 in (8.38 cm)	
Package 1 Width	1.60 in (4.06 cm)	
Package 1 Length	3.20 in (8.13 cm)	
Package weight(Lbs)	9.12 oz (258.55 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	5	
Package 2 Height	3.30 in (8.382 cm)	
Package 2 Width	2.70 in (6.858 cm)	
Package 2 Length	7.70 in (19.558 cm)	
Package 2 Weight	2.941 lb(US) (1.334 kg)	
Unit Type of Package 3	CAR	
Number of Units in Package 3	50	
Package 3 Height	8.20 in (20.828 cm)	
Package 3 Width	8.00 in (20.32 cm)	
Package 3 Length	17.20 in (43.688 cm)	
Package 3 Weight	30.05 lb(US) (13.63 kg)	

## **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	19
Environmental Disclosure	Product Environmental Profile

#### **Use Better**


Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

#### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

## **Technical Illustration**

## **Dimensions**



# Product data sheet

QO240

Image of product / Alternate images

**Alternative** 

## **Technical Benefits** Thermal Magnetic Breaker



Miniature circuit breaker rated at 40A



Easy plug on circuit breaker that's compatible with Square D™ QO Loadcenters





Protects against overloads and short-circuits



The current capacity that this circuit breaker is able to interrupt before breaking is 10kA



Quickly identify tripped breakers with our Visi-Trip indicator



Compatible with QO electrical panels and CSEDs with 2 spaces









Qwik-Open\* technology - Overload and Short circuit protection



Market-leading circuit protection



