QOB2100

Mini circuit breaker, QO, 100A, 2 pole, 120/240VAC, 10kA, bolt on





Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	100 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 KA 120/240 V AC	
	10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 4AWG 2/0 copper or aluminium	
Tightening Torque	49.6 lbf.in (5.6 N.m)	
Height	3.5 in (89 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.750 lb(US) (0.340 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200015
Discount Schedule	0DE2
GTIN	785901019688
Returnability	Yes
Country of origin	MX

Packing Units

PCE
1
1.600 in (4.064 cm)
3.300 in (8.382 cm)
3.900 in (9.906 cm)
12.000 oz (340.194 g)
CAR
51
3.900 in (9.906 cm)
13.900 in (35.306 cm)

Package 2 Length	20.800 in (52.832 cm)
Package 2 Weight	37.249 lb(US) (16.896 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

18 months

Warranty