



Mini circuit breaker, QO, 20A, 2 pole, 120/240VAC, 10kA, bolt on

QOB220

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker	
Range	QO	
Current Rating	20 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Bolt-on	
Number of Poles	2P	
Circuit Breaker Type	Standard	
Ratings	HACR rated	
Electrical Connection	Pressure plate	

Complementary

Interrupt Rating	10 kA 120/240 V AC 10 kA 120 V AC	
Number of Panel Spaces	2	
Wire Size	AWG 14AWG 8 copper or aluminium	
Tightening Torque	35.4 lbf.in (4 N.m)	
Height	3.0 in (76 mm)	
Width	1.5 in (38 mm)	
Depth	2.9 in (74 mm)	
Net Weight	0.549 lb(US) (0.249 kg)	

Environment

Certifications	UL Listed CSA	
Ambient Rating	104 °F (40 °C)	

Ordering and shipping details

Category	US10DE200015
Discount Schedule	0DE2
GTIN	785901416869
Returnability	Yes
Country of origin	MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

_	
Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.60 in (6.6 cm)
Package 1 Width	1.50 in (3.81 cm)
Package 1 Length	3.00 in (7.62 cm)
Package weight(Lbs)	8.80 oz (249.48 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	3.30 in (8.382 cm)
Package 2 Width	1.50 in (3.81 cm)
Package 2 Length	7.60 in (19.304 cm)
Package 2 Weight	2.80 lb(US) (1.27 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	8.20 in (20.828 cm)
Package 3 Width	7.90 in (20.066 cm)
Package 3 Length	17.10 in (43.434 cm)
Package 3 Weight	28.451 lb(US) (12.905 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	19
Environmental Disclosure	Product Environmental Profile

Use Better


Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	Af42fb01-813d-40c0-ae28-b8b3299dbc99
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free product

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions



Dimensions are approximate. Refer to technical documentation for additional deta

Image of product / Alternate images

Alternative

Technical Benefits Thermal Magnetic Breaker



