

QOB240

Mini circuit breaker, QO, 40A, 2 pole,
120/240VAC, 10kA, bolt on



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	40 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	HACR rated
Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 KA 120/240 V AC 10 kA 120 V AC
Number of Panel Spaces	2
Wire Size	AWG 8...AWG 2 copper or aluminium
Tightening Torque	44.3 lbf.in (5 N.m)
Height	3.1 in (79 mm)
Width	1.5 in (38 mm)
Depth	2.9 in (74 mm)
Net Weight	0.600 lb(US) (0.272 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US10DE200015
Discount Schedule	0DE2
GTIN	785901416944
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	1.50 in (3.81 cm)
Package 1 Length	3.300 in (8.382 cm)
Package 1 Weight	9.600 oz (272.155 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	1200
Package 2 Height	22.0000000000 in (55.88 cm)
Package 2 Width	40.0000000000 in (101.6 cm)

Package 2 Length	42.0000000000 in (106.68 cm)
Package 2 Weight	753.0005 lb(US) (341.555 kg)
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Height	3.200 in (8.128 cm)
Package 3 Width	1.50 in (3.81 cm)
Package 3 Length	7.700 in (19.558 cm)
Package 3 Weight	3.0005 lb(US) (1.361 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------