

Project:		Type:
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

WPS GEN 4

CLASSIC WALL PACK

Selectable color temperature (3 000/4 000/5 000 K) Power selectable Integrated Photocell Multi-Voltage (120-347 V)

ORDERING INFORMATION

Order code: 68314

Model number: WPS-PS40-Q-3C UPC: 069549007307 **DLC** unique ID: PLW61NEJG50K

Case quantity:

PHYSICAL DATA

Dimensions: 14.37" x 9.33" x 7.36" (365 mm x 237 mm x 187 mm)

Aluminium die-cast **Housing material:**

Lens Material: Prismatic tempered glass lens

Some of the configurations comes with a button type photocell that can be turned off Photocell:

by using the internal switch if needed

PERFORMANCE DATA

Watts (W): 25/30/40 Volts (VAC): 120 - 347 Colour temperature (K)1: 3 000/4 000/5 000 Lumen output (lm)2: 3 580 - 5 606 Efficiency (Im/W): 140 - 150 CRI: >80 Finish: Bronze Photocell: Yes Dimming (Yes/No): Yes LED current (mA) 850 Power factor: 0.90 THD (%): 20

Operating temp. range: -40°C to 50°C

COMPATIBLE ACCESSORIES

Order code	Description	
68370 18" Bronze metal backplate		
68371	Bronze glareshield	
68372 Stainless Steel wireguard		

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications Data is based upon tests performed in a controlled environment.

Actual performance can vary depending on operating conditions. Specifications are subject to change without notice











fixture

















Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.




¹ Typical colour temperature range: +/- 5 %

men values are derived from photometric testing. Initial lumens range: +/- 10 %



DIMENSIONS



SELECTABLE COLOR TEMPERATURE AND ON/OFF INTEGRATED PHOTOCELL



POWER SELECTABLE


	Order code	
Power Selection	68314	68315
1	25 W	60 W
2	30 W	80 W
3	40 W	100 W



PHOTOMETRIC DATA¹

68314 • WPS-PS40-Q-3C • 5 403.5 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Lamp
0-30	820.9	15.2%
0-40	1 349.6	25%
0-60	2 629.8	48.7%
60-90	1 784.2	33%
70-100	1 564.6	29%
90-120	874.9	16.2%
0-90	4 414.1	81.7%
90-180	989.5	18.3%
0-180	5 403.5	100%

Illuminance at a distance

	Center beam fc		Beam width	
8.3'	16.2	A	25.7'	22.2'
16.7'	4.00		51.8'	44.7'
25.0'	1.79		77.5'	66.9'
33.31	1.01		103.2'	89.1'
41.7'	0.64		129.2'	111.6'
50.0'	0.45		155.0'	133.8'
	Vert. spread: Horiz. spread:	114.3° 106.4°		

¹ Complete IES files available on our website.



Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

