

Project: _____ Type: _____
 Drawn by: _____ Catalogue #: _____ Date: _____

Individual Spec Sheet

LPDL CCT SELECTABLE

LOW PROFILE DOWNLIGHT

5 color temperature selection

ORDERING INFORMATION

Order code: 68731
Model number: LPDL3/RND/7W/5CCT/WH
UPC: 069549018747
Case quantity: 24

PHYSICAL DATA

Size in (cm): 3 (7.62)
Shape: Round
Finish: White
Lens type: Frosted Polycarbonate

PERFORMANCE DATA

Watts (W): 7
Volts (V AC): 120
Color temp. (K):¹ 2 700/3 000/3 500/4 000/5 000
Lumen output (lm):² 420
Efficacy (lm/W): 60
CRI: 80+
Life L70 (h):³ 50 000
Beam angle (°): 110
Environment: Damp location
THD (%): <20
Power factor: >0.9
Frequency (Hz): 60
Operating temp. range: -20 °C to 45 °C (-4 °F to 113 °F)
Dimmable: Yes

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from Energy Star reported data. Initial lumens range: +/- 10 %.

³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations.

COMPATIBLE ACCESSORIES

Order code	Model number	Type
66056	ACC/MPLATE/3.625IN/ADJ/STD	Adjustable mounting plate
66049	ACC/MPLATE/3.625IN/SQR/STD	Square mounting plate
66142	ACC/3/VAPOR BARRIER/STD	Vapor barrier extender
66820	ACC/MPLATE/3.625IN/HANG.BARS/STD	Mounting plate with hanger bars




This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
 Data is based upon tests performed in a controlled environment.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

COMPATIBLE DIMMERS

Brand	Model
LEVITON	IPL06, 6674, DSL06-1ZL, DSM10-1LZ, IPE04-1LZ, DDMX1
LUTRON	PD-5NE, PD-6WCL, RRD-6NA, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVRP-253, SELV-300P, MACL-153P
COOPER	AAL06
LEGRAND	RH703PTUTC

NOTE: The above table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation. Some dimmers may require more than one product for stable operation. The maximum number of products is determined by the dimmer wattage rating with LEDs. Be careful, these dimmers have different ratings depending on the product type. Again, refer to the dimmer installation instructions.


DIMENSIONS



PHOTOMETRIC DATA¹

68731 • LPDL3/RND/7W/5CCT/WH • 3 000 K • 610.7 lm

Polar candela distribution



Zonal lumen summary

Zone	Lumens	% Fixture
0-30	164.2	26.9
0-40	271.7	44.5
0-60	482.5	79
60-90	128.2	21
0-90	610.7	100

Illuminance at a distance

Center beam fc	Beam width
1.7'	5.1'
3.3'	9.8'
5.0'	14.9'
6.7'	19.9'
8.3'	24.7'
10.0'	29.7'

Vert. spread: 112.2°
Horiz. spread: 112.6°

¹ Complete IES files available on our website.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
Company: _____
Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.