

# FFI

## FLOOR INSERT FAN HEATER



### HEAT FROM AN UNEXPECTED PLACE

The FFI is the perfect solution when there's no wall space available, such as under low windows, bay windows and patio doors. It's also a great fit for offices, narrow entryways and bathrooms. It can be recessed between floor joists. Its grille is solidly constructed of rigid aluminum to withstand foot traffic. Installation at construction sites is easy thanks to its compact design. This floor insert fan heater can also be recessed into concrete floors.

- **DURABLE ALUMINUM GRILLE**
- **EASILY CONCEALED**
- **EASY INSTALLATION**
- **CAN BE RECESSED INTO CONCRETE FLOORS**

#### COLOURS

- **standard:** white
- **Orora (optional):** refer to [www.stelpro.com/en-CA/Orora](http://www.stelpro.com/en-CA/Orora)

#### FINISH

- epoxy-polyester powdercoat

#### MANUFACTURING

- durable 16-gauge steel cabinet and 9-gauge aluminum extruded grille
- protective wire mesh to prevent foreign objects from entering the interior of the unit
- 80 CFM capacity fan
- thermal protection with automatic reset

#### ELEMENT

- tubular element sheathed with spiral-wound fins for improved heat dissipation

#### CONTROL

- wall thermostat only (not included) – the use of an electronic thermostat is strongly recommended

#### INSTALLATION

- recessed between floor joists
- in a concrete floor without framing
- large wiring compartment

#### WARRANTY

- five years

#### IDEAL FOR:

in front of a patio door, office, narrow entryway, bathroom

# °STELPRO

Stelpro reserves the right to modify at any time the description, manufacturing, or price of its products. Additionally, Stelpro may apply restocking fees or refuse a refund based on one or more of the following criteria: optional color, custom product, assembly with low-demand options. For the latest product information and prices regarding the products, please visit the website [www.stelpro.com](http://www.stelpro.com).



FC\_FFI\_EN\_160824



## TECHNICAL SPECIFICATIONS

PRODUCT	POWER	VOLTAGE	THROW DISTANCE		HEAT RISE		WEIGHT	
CODE	WATTS	VOLTS	M	FT	°C	°F	KG	LB
<b>FFI1002W</b>	1000/750	240/208	2	6'5"	60	108	8.1	18
<b>FFI1502W</b>	1500/1125	240/208	2	6'5"	66	119	8.1	18

Consult the optional colours chart or contact your Stelpro representative for all other colours.

## TECHNICAL DRAWINGS

