

SWT

MECHANICAL THERMOSTAT – LINE VOLTAGE

- COLOURS
- white, soft white

- FINISH
- molded plastic

- VOLTAGE
- 22 A @ 120-277 Vac
 - 1/2 hp

- CONTROL
- two-wire connection (single pole model) or four-wire connection (double pole model)
 - temperature in degrees Celsius
 - off position (double pole model)

- TEMPERATURE RANGE
- 10 to 30 °C (50 to 90 °F)

- WARRANTY
- one year

PRODUCT	DESCRIPTION	PRICE
SWT1C*	SINGLE POLE THERMOSTAT (CELSIUS)	14.00
SWT2C	DOUBLE POLE THERMOSTAT (CELSIUS)	21.00

*Add SW for soft white.
 Dimensions: 2 29/32 in. (74 mm) wide, 4 37/64 in. (116 mm) high and 1 9/64 in. (29 mm) deep



RJ32

MECHANICAL THERMOSTAT – LINE VOLTAGE

- COLOURS
- white or beige

- VOLTAGE
- 22 A @ 120, 208 or 240 Vac / 19 A @ 277 Vac

- CONTROL
- two-wire connection (single pole model) or four-wire connection (double pole model)
 - temperature in degrees Celsius

- TEMPERATURE RANGE
- 5 to 32 °C (41 to 90 °F)

- WARRANTY
- one year

PRODUCT	DESCRIPTION	COLOUR	PRICE
RJ32W1	SINGLE POLE THERMOSTAT	WHITE	17.00
RJ32B1	SINGLE POLE THERMOSTAT	BEIGE	19.00
RJ32W2	DOUBLE POLE THERMOSTAT	WHITE	24.00

Dimensions: 4 1/2 in. (114.3 mm) wide, 2 3/4 in. (69.9 mm) high and 2 1/4 in. (57.2 mm) deep



°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.