

SBB

COMPACT MULTIPURPOSE BASEBOARD



A BREAKTHROUGH IN PERFORMANCE

Looking for the sleekest baseboard to heat your living room, kitchen, bedroom or office that won't take up too much wall space? The compact multipurpose SBB baseboard fits the bill perfectly since it comes in three watt densities. The SBB can be up to 30% shorter than conventional baseboards without sacrificing power and safety.

**UP TO 30% SHORTER THAN
CONVENTIONAL BASEBOARDS**
FREES UP PRECIOUS WALL SPACE

**OPTIMAL PERFORMANCE
AND SAFETY**

**OFFERED IN THREE DIFFERENT
WATT DENSITIES**
MEETS THE NEEDS OF ANY PROJECT
IN THE HOME OR OFFICE

TOTALLY QUIET

COLOURS

- **standard:** white, soft white
- **ORORA (optional):** refer to www.stelpro.com/en-CA/orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 18-gauge steel one-piece front
- full-length thermal protection with automatic reset
- discreet air inlet and top air discharge to maximize air flow
- full-length wireway

ELEMENT

- single tubular, stainless steel sheathed element with boxed aluminum fins for improved heat dissipation securely fastened at its centre, floating in nylon sleeves at each end, eliminating expansion and contraction noises

CONTROL

- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended
- built-in single or double pole mechanical thermostat installed in the left or right junction box (optional)
- built-in tamper-proof single or double pole mechanical thermostat installed in the left or right junction box (optional)
- low voltage relay kit installed in the right junction box only (optional)

INSTALLATION

- surface mounted
- wiring compartment at both ends of unit

WARRANTY

- five years, *lifetime warranty on the heating element (for original owner)

IDEAL FOR:

kitchen, living room, bedroom, basement, office

PART OF THE SHC FAMILY OF PRODUCTS

NEED A CONVECTOR?

SHC



°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SBB_EN_311018

TECHNICAL SPECIFICATIONS

DENSITY OF 350 W PER LINEAR FOOT *			DENSITY OF 275 W PER LINEAR FOOT *			DENSITY OF 200 W PER LINEAR FOOT *			VOLTAGE	LENGTH		WEIGHT	
CODE	WATTS	PRICE	CODE	WATTS	PRICE	CODE	WATTS	PRICE	VOLTS	MM	IN.	KG	LB
SBB0501	500	52.00	SBBM0401	400	68.00	SBBL0301	300	68.00	120	609	24	2.6	5.7
SBB0508	500	44.00	SBBM0408	400	60.00	SBBL0308	300	60.00	208	609	24	2.6	5.7
SBB0502	500/375	42.00	SBBM0402	400/300	58.00	SBBL0302	300/225	58.00	240/208	609	24	2.6	5.7
SBB0503	500	52.00	---	---	---	---	---	---	347	609	24	2.6	5.7
SBB0751	750	58.00	SBBM0601	600	74.00	SBBL0451	450	74.00	120	762	30	3	6.7
SBB0758	750	50.00	SBBM0608	600	66.00	SBBL0458	450	66.00	208	762	30	3	6.7
SBB0752	750/560	48.00	SBBM0602	600/450	64.00	SBBL0452	450/340	64.00	240/208	762	30	3	6.7
SBB0753	750	58.00	SBBM0603	600	74.00	SBBL0453	450	74.00	347	762	30	3	6.7
SBB1001	1000	68.00	SBBM0801	800	84.00	SBBL0601	600	84.00	120	914	36	3.5	7.7
SBB1008	1000	57.00	SBBM0808	800	73.00	SBBL0608	600	73.00	208	914	36	3.5	7.7
SBB1002	1000/750	55.00	SBBM0802	800/600	71.00	SBBL0602	600/450	71.00	240/208	914	36	3.5	7.7
SBB1003	1000	68.00	SBBM0803	800	84.00	SBBL0603	600	84.00	347	914	36	3.5	7.7
SBB1006	1000	68.00	---	---	---	---	---	---	600	914	36	3.5	7.7
SBB1251	1250	79.00	SBBM1001	1000	95.00	SBBL0751	750	95.00	120	1066	42	4	8.7
SBB1258	1250	66.00	SBBM1008	1000	82.00	SBBL0758	750	82.00	208	1066	42	4	8.7
SBB1252	1250/940	64.00	SBBM1002	1000/750	80.00	SBBL0752	750/560	80.00	240/208	1066	42	4	8.7
SBB1253	1250	79.00	SBBM1003	1000	95.00	SBBL0753	750	95.00	347	1066	42	4	8.7
SBB1256	1250	79.00	SBBM1006	1000	95.00	---	---	---	600	1066	42	4	8.7
SBB1501	1500	87.00	SBBM1201	1200	103.00	SBBL0901	900	103.00	120	1219	48	4.4	9.7
SBB1508	1500	72.00	SBBM1208	1200	88.00	SBBL0908	900	88.00	208	1219	48	4.4	9.7
SBB1502	1500/1125	70.00	SBBM1202	1200/900	86.00	SBBL0902	900/675	86.00	240/208	1219	48	4.4	9.7
SBB1503	1500	87.00	SBBM1203	1200	103.00	SBBL0903	900	103.00	347	1219	48	4.4	9.7
SBB1506	1500	87.00	SBBM1206	1200	103.00	SBBL0906	900	103.00	600	1219	48	4.4	9.7
---	---	---	SBBM1401	1400	120.00	SBBL1051	1050	120.00	120	1371	54	4.9	10.7
SBB1758	1750	86.00	SBBM1408	1400	102.00	SBBL1058	1050	102.00	208	1371	54	4.9	10.7
SBB1752	1750/1310	83.00	SBBM1402	1400/1050	99.00	SBBL1052	1050/790	99.00	240/208	1371	54	4.9	10.7
SBB1753	1750	104.00	SBBM1403	1400	120.00	SBBL1053	1050	120.00	347	1371	54	4.9	10.7
SBB1756	1750	104.00	SBBM1406	1400	120.00	SBBL1056	1050	120.00	600	1371	54	4.9	10.7
---	---	---	SBBM1601	1600	131.00	SBBL1201	1200	131.00	120	1524	60	5.3	11.7
SBB2008	2000	93.00	SBBM1608	1600	109.00	SBBL1208	1200	109.00	208	1524	60	5.3	11.7
SBB2002	2000/1500	90.00	SBBM1602	1600/1200	106.00	SBBL1202	1200/900	106.00	240/208	1524	60	5.3	11.7
SBB2003	2000	115.00	SBBM1603	1600	131.00	SBBL1203	1200	131.00	347	1524	60	5.3	11.7
SBB2006	2000	115.00	SBBM1606	1600	131.00	SBBL1206	1200	131.00	600	1524	60	5.3	11.7
---	---	---	---	---	---	SBBL1351	1350	142.00	120	1676	66	5.8	12.7
SBB2258	2250	103.00	SBBM1808	1800	119.00	SBBL1358	1350	119.00	208	1676	66	5.8	12.7
SBB2252	2250/1690	100.00	SBBM1802	1800/1350	116.00	SBBL1352	1350/1010	116.00	240/208	1676	66	5.8	12.7
SBB2253	2250	126.00	SBBM1803	1800	142.00	SBBL1353	1350	142.00	347	1676	66	5.8	12.7
SBB2256	2250	126.00	SBBM1806	1800	142.00	SBBL1356	1350	142.00	600	1676	66	5.8	12.7
---	---	---	---	---	---	SBBL1501	1500	153.00	120	1828	72	6.2	13.7
SBB2508	2500	111.00	SBBM2008	2000	127.00	SBBL1508	1500	127.00	208	1828	72	6.2	13.7
SBB2502	2500/1875	108.00	SBBM2002	2000/1500	124.00	SBBL1502	1500/1125	124.00	240/208	1828	72	6.2	13.7
SBB2503	2500	137.00	SBBM2003	2000	153.00	SBBL1503	1500	153.00	347	1828	72	6.2	13.7
SBB2506	2500	137.00	SBBM2006	2000	153.00	SBBL1506	1500	153.00	600	1828	72	6.2	13.7

Add W for white or SW for soft white (consult the optional colours chart or contact your °STELPRO representative for all other colours).

* Average densities shown.

Models also available in 277 V and 480 V.

--- not available

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SBBT1*	built-in single pole thermostat [120 V-600 V]	24.00
SBBT2*	built-in double pole thermostat [120 V-600 V]	28.00
SBBT1TP**	built-in tamper-proof single pole thermostat [120 V-600 V]	40.00
SBBT2TP**	built-in tamper-proof double pole thermostat [120 V-600 V]	44.00
SBBRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]	48.00
SBBRE156*	built-in electronic low voltage relay [6 A @ 600 V]	81.00
SBBRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]	62.00
SBBRM240T*	built-in electromechanical relay c/w transformer 24 V [6000 W @ 240 V and 5200 W @ 208 V]	67.00
SBBRM347T*	built-in electromechanical relay c/w transformer 24 V [6000 W @ 347 V]	70.00
SBBRM347C*	built-in electromechanical relay w/o transformer 24 V [6000 W @ 120 V-347 V]	52.00
SBBR841C1151*	built-in electromechanical relay with transformer 24 V [6000 W @ 600 V]	122.00
SBBR841D1036*	built-in electromechanical relay w/o transformer 24 V [6000 W @ 600 V]	106.00

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.

* Add W for white or BK for black (white unit supplied with a white knob and soft white or optional coloured units supplied with a black knob).

* Factory installed

* Factory installation is strongly recommended

TECHNICAL DRAWINGS



