

ELECTRONIC THERMOSTAT

STE302NP SERIES

1 SINGLE PROGRAMMING

3000 W

INSTALLATION AT YOUR FINGERTIPS!

Thanks to its innovative wall support, the °STELPRO STE302NP thermostat is quick and easy to install. It can be used to control electric heating units with or without fans. It also allows you to lower the temperature at a specified time of the day to ensure absolute comfort, either during nighttime or business hours.



SIMPLE 4-STEP PROGRAMMING

LOWER THE TEMPERATURE AT NIGHT AND AUTOMATICALLY RETURN TO THE SELECTED TEMPERATURE DURING THE DAY



INCREASED SAVINGS AND COMFORT

INCOMPARABLE ACCURACY



BACKLIT SCREEN

MAY BE USED AS A NIGHTLIGHT



CONSUMPTION SAVINGS

ENERGY SAVINGS OF MORE THAN 30% WITH DAY/NIGHT TEMPERATURE REDUCTION OF 4.5 °C (8 °F)

COLOUR

white

FINISH

molded plastic

WATTAGE & VOLTAGE

150 W to 1500 W @ 120 V / 260 W to 2600 W @ 208 V / 300 W to 3000 W @ 240 V

CONTROL

- 2-wire connection
- acts like a programmable thermostat by automatically lowering the temperature once per 24-hour period (Single programming mode)
- compatible with forced-air units (Fan mode)
- frost-free warning
- lock option at a maximum temperature set point (Security mode)
- display in either Celsius or Fahrenheit

ACCURACY

accurate ambient temperature control of ± 0.1 °C (0.18 °F)

TEMPERATURE RANGE

between 3 and 30 °C (37 to 86 °F)

DESIGNED FOR



AND MORE...

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
STE302NPWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60	BOX	31.00

DIMENSIONS: width of 4 7/8 in. (124 mm), height of 4 7/8 in. (124 mm) and depth of 1 1/8 in. (29 mm)