

STE302NP

ELECTRONIC THERMOSTAT – SINGLE PROGRAMMING

3000 W



DESIGNED FOR:



PRACTICAL AND EFFICIENT!

Thanks to its innovative wall support, the °STELPRO STE302NP thermostat is quick and easy to install. It can be used to control electric heating units with or without fans. It also allows you to lower the temperature at a specified time of the day to ensure absolute comfort, either at night or during business hours.



SIMPLE TO USE AND INSTALL



INCREASED SAVINGS AND COMFORT INCOMPARABLE ACCURACY



BACKLIT SCREEN CAN BE USED AS A NIGHTLIGHT



ELECTRICITY SAVINGS ENERGY SAVINGS OF 10-15% DEPENDING ON USE*

COLOUR

- white

FINISH

- molded plastic

WATTAGE AND VOLTAGE

- 150 W to 1500 W @ 120 V
- 260 W to 2600 W @ 208 V
- 300 W to 3000 W @ 240 V

CONTROL

- two- or four-wire connection
- acts like a programmable thermostat by automatically lowering the temperature once per 24-hour period (Single programming mode)
- compatible with forced-air units (Fan mode)

- frost-free warning
- lock option at a maximum temperature setpoint (Security mode)
- display in Celsius or Fahrenheit

ACCURACY

- accurate ambient temperature control of ± 0.1 °C (0.18 °F)
- CSA C828-13

TEMPERATURE RANGE

- 3 to 30 °C (37 to 86 °F)

WARRANTY

- three years
- * independent study

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
STE302NPWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60	BOX	34.00

Dimensions: 4 7/8 in. (124 mm) wide, 4 7/8 in. (124 mm) high and 1 1/8 in. (29 mm) deep

°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_STE302NP_EN_260318