

# ELECTRONIC THERMOSTAT

STE302P SERIES

**M** MULTIPLE PROGRAMMING

3000 W

## THE SMART, EFFICIENT AND ECOLOGICAL CHOICE

Cost-saving programming, that's what the STE302P thermostat has to offer. Life just got both simpler and more comfortable thanks to its Preprogrammed mode that allows you to easily and quickly program the desired temperature. Offering 18 predefined programs, the user can easily select among the most commonly used settings or program their own custom settings.



- 18 EASY PROGRAMMING**  
INCLUDES 18 PREPROGRAMMED PRESETS IN "PRE-PROG" MODE
- ± 0.1°C INCREASED SAVINGS AND COMFORT**  
INCOMPARABLE ACCURACY
- ANTICIPATED START**  
REACH THE SELECTED TEMPERATURE AT PRECISELY THE PROGRAMMED TIME
- 5-2 5-2 DAY PROGRAMMING**
- BACKLIT SCREEN**  
MAY BE USED AS A NIGHTLIGHT

**MORE THAN 30% CONSUMPTION SAVINGS**  
ENERGY SAVINGS OF MORE THAN 30% WITH DAY/NIGHT TEMPERATURE REDUCTION OF 4.5 °C (8 °F)

DESIGNED FOR



AND MORE...

### COLOUR

white

### FINISH

molded plastic

### WATTAGE & VOLTAGE

150 W to 1500 W @ 120 V / 260 W to 2600 W @ 208 V / 300 W to 3000 W @ 240 V

### CONTROL

- 2-wire connection
- compatible with forced-air units (Fan mode)
- easily choose the desired preprogramming with one button
- able to program 4 periods a day during the week and 4 others per day during the weekend, for a maximum of 8/week
- anticipated start (the thermostat reaches the desired temperature at the requested hour)
- frost-free warning
- lock option at a minimum and maximum temperature set point (Security mode)
- protection against power failure (2 hours)
- the hour can be displayed in 12 or 24-hour mode
- display in either Celsius or Fahrenheit

### ACCURACY

accurate ambient temperature control of ± 0.1 °C (0.18 °F)

### TEMPERATURE RANGE

between 3 and 30 °C (37 to 86 °F)

## TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
	CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES		
STE302PWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60	BOX	42.00

DIMENSIONS: width of 4 7/8 in. (124 mm), height of 4 7/8 in. (124 mm) and depth of 1 1/8 in. (29 mm)



\*STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. Returns are not accepted for orders of products with optional colours. For all the latest models and updated prices, please refer to our web site at [www.stelpro.com](http://www.stelpro.com).