

ELECTRONIC THERMOSTAT


STE402NP/403NP SERIES

HEAT LARGE ROOMS WITH EASE

The STE402NP electronic thermostat allows temperature control with a high degree of accuracy. It has a useful digital screen displaying the ambient temperature and the set point simultaneously. It has a Security mode which enables you to block the set point at a maximum temperature. It's simple and safe!

1 SINGLE PROGRAMMING

4000 W



ALSO AVAILABLE
STE403NP - 347 V model



SIMPLE 4-STEP PROGRAMMING

LOWER THE TEMPERATURE AT NIGHT AND AUTOMATICALLY RETURN TO THE SELECTED TEMPERATURE DURING THE DAY



INCREASED SAVINGS AND COMFORT

INCOMPARABLE ACCURACY



BACKLIT SCREEN*

MAY BE USED AS A NIGHTLIGHT



CONSUMPTION SAVINGS

ENERGY SAVINGS OF MORE THAN 30% WITH DAY/NIGHT TEMPERATURE REDUCTION OF 4.5 °C (8 °F)

COLOUR

white (soft white is available only for the STE402NP model and packaged in a clamshell)

FINISH

molded plastic

WATTAGE & VOLTAGE

150 W to 2000 W @ 120 V / 260 W to 3475 W @ 208 V /
300 W to 4000 W @ 240 V / 350 W to 4600 W @ 277 V (STE403NP) /
400 W to 5750 W @ 347 V (STE403NP)

CONTROL

- 2-wire connection
- acts like a programmable thermostat by automatically lowering the temperature once per 24-hour period (Single programming mode)
- compatible with forced-air units (Fan mode)
- frost-free warning
- lock option at a maximum temperature set point (Security mode)
- display in either Celsius or Fahrenheit


ACCURACY

accurate ambient temperature control of ± 0.1 °C (0.18 °F)

TEMPERATURE RANGE

between 3 and 30 °C (37 to 86 °F)

DESIGNED FOR



AND MORE...

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOUR	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ			
STE402NPWB+	150/260/300	2000/3475/4000	120/208/240	16.7	50/60	WHITE	BOX	37.00
STE402NPBW+	150/260/300	2000/3475/4000	120/208/240	16.7	50/60	SOFT WHITE	CLAMSHELL	41.50
STE403NPW24	150/260/300/350/400	2000/3475/4000/4600/5750	120/208/240/277/347	16.7	50/60	WHITE	BOX	97.00

DIMENSIONS: width of 4 7/8 in. (124 mm), height of 4 7/8 in. (124 mm) and depth of 1 3/8 in. (29 mm)
(STE403NP: width of 4 1/2 in. (114 mm), height of 4 7/8 in. (124 mm) and depth of 1 3/8 in. (35 mm))

* Except STE403NP model

STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. Returns are not accepted for orders of products with optional colours.
For all the latest models and updated prices, please refer to our web site at www.stelpro.com.

