STE402NP/403NP

ELECTRONIC THERMOSTAT - SINGLE PROGRAMMING

4000 W











PRACTICAL AND EFFICIENT!

The STE402NP electronic thermostat allows you to precisely control the temperature. It has a Security mode that lets you program a maximum temperature setpoint. It's simple and safe!



SIMPLE TO USE AND INSTALL



GREAT POWER 4000 W



INCREASED SAVINGS AND COMFORT





BACKLIT SCREEN[†]
CAN BE USED AS A NIGHTLIGHT



COLOUR

 white (soft white is available only for the STE402NP model and packaged in a clamshell)

FINISH

• molded plastic

WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 260 W to 3475 W @ 208 V
- 300 W to 4000 W @ 240 V
- 350 W to 4600 W @ 277 V (STE403NP)
- 400 W to 5750 W @ 347 V (STE403NP)

CONTROL

- two- or four-wire connection
- acts like a programmable thermostat by automatically lowering the temperature once per 24-hour period (Single programming mode)

- compatible with forced-air units (Fan mode)
- · frost-free warning
- lock option at a maximum temperature setpoint (Security mode)
- · display in Celsius or Fahrenheit

ACCURACY

- accurate ambient temperature control of ± 0.1 °C (0.18 °F)
- CSA C828-13

TEMPERATURE RANGE

• 3 to 30 °C (37 to 86 °F)

WARRANTY

- · three years
- * independent study
- † except STE403NP model

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOUR	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ			
STE402NPWB+	150/260/300	2000/3475/4000	120/208/240	16.7	50/60	WHITE	вох	38.00
STE402NPSW+	150/260/300	2000/3475/4000	120/208/240	16.7	50/60	SOFT WHITE	CLAMSHELL	43.00
STE403NPW24	150/260/300/350/400	2000/3475/4000/4600/5750	120/208/240/277/347	16.7	50/60	WHITE	BOX	102.00

Dimensions: 4 7/8 in. (124 mm) wide, 4 7/8 in. (124 mm) high and 1 3/8 in. (29 mm) deep (STE403NP: 4 1/2 in. (114 mm) wide, 4 7/8 in. (124 mm) high and 1 3/8 in. (35 mm) deep)



