

SPECIFICATIONS



Day Spa Steam Generator

Day Spa 400 Series Standard Equipment:

- Designed for Multiple steam room use, 2 to 4 Rooms.
- 3 Phase unit is available on 400 Series Generators.
- Includes Steam Distribution System Module to deliver steam to rooms independently. See separate Rough-in Guide.
- Designed for commercial use.
- Large capacity tank size.
- Unit has 208-240 volt power connections to be installed by your licensed electrician.
- Superior heating elements low watt density.
- Includes Stainless Steel drip pan.

- Can be plumbed up to 50 ft. from the steam room without upsizing the generator.
- Stainless steel construction throughout.

- Split tank technology enhances performance and life-span.
- New style Polished Chrome Steam Head.
- Hardware Kit provided.
- Temp Sensor is built into controller.
- Optional Front Desk Sentinel Control is available & may be located up to 100' of cable run from the generator.

Installation Notes:

Generator must be installed by a licensed electrician. DS-X-400 Series Generators MUST have two independent breakers. Install this generator according to the installation guide supplied. Follow all local plumbing and electrical codes. Unit must be accessible for service and maintenance. Generator is factory sized: L x W x H = Steam Room Cubic Feet = 400 Cu. Ft. max. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

Product Specification Basics:

The steam generator unit dimensions are approximately 18-3/4"L x 13-3/4"W x 16"H in dimension. The generator shall be made from stainless steel and include: SmartSteam, PowerFlush and a Split Tank.

Shipping Information:

Weight 46 lbs.	
Length22 in.	
Width18 in.	
Height17 in.	

For any further assistance please contact ThermaSol at 800.776.0711 or sales@thermasol.com

Visit www.thermasol.com for a complete product definition



11.540-11.570

4.0-5.0 M