

MEDIUM DUTY TOGGLES (Cont.)



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125-250VAC	Actuator Style	Actuator Material	Bushing Length	Mounting Hole	Terminal Type	Hardware	Spec. Drawing Page No.	
35-854	1	On		Off	SPST	6	3		Bat	Black Plastic	0.342"	0.500"	WL	KN, ID	H-11 A
35-1076	2	Off		(On)	SPST	6	3	1/4	Bat	Metal	0.465"	0.500"	Screw	N, KN, FN, Sc	H-11 B
35-1114	2	On		On	SPDT	6	3	1/4	Bat	Metal	0.465"	0.500"	Screw	N, KN, FN, Sc	H-11 B
35-1116	2	On		(On)	SPDT	6	3	1/4	Bat	Brass	0.465"	0.500"	Screw	N, KN, FN, Sc	H-11 B
35-3035	3	On		Off	SPST	6	3		Bat	Brass	0.325"	0.500"	Screw	2 N	H-11 C
35-119	4	On		Off	SPST	10	5	1/2	Bat	Metal	0.500"	0.500"	QC .250"	N, KN	H-11 D
35-120	4	On		On	SPDT	10	5	1/2	Bat	Metal	0.500"	0.500"	QC .250"	N, KN	H-11 D
35-180	5	On		Off	SPST	10	5	1/2	Paddle	Black Plastic	0.280"	0.500"	QC .250"/Sd	FN, NN	H-11 E
35-182	5	On		On	SPDT	10	5	1/2	Paddle	Black Plastic	0.280"	0.500"	QC .250"/Sd	FN, NN	H-11 E
35-184	5	On	Off	On	SPDT	10	5	1/2	Paddle	Black Plastic	0.280"	0.500"	QC .250"/Sd	FN, NN	H-11 E
35-3050	6	On		Off	SPST	10	4	1/3	Bat	Brass	0.325"	0.500"	WL	2 N	H-11 F
35-112	7	On		Off	DPST	15	10		Bat	Metal	0.468"	0.500"	Solder	N, KN	H-11 G
35-152	7	On		On	DPDT	15	10		Bat	Metal	0.468"	0.500"	Solder	N, KN	H-11 G
35-3127	11	(On)	Off	(On)†	DPDT	15	10	1/2	Bat	Metal	0.465"	0.500"	QC .250"	FN, N	H-11 H
35-3153	8	(On)	Off	(On)	SPDT	15	10	3/4	Paddle	Black Nylon	0.379"	0.500"	QC .250"	FN, NN	H-11 I
35-3169	9	(On)	Off	(On)	SPDT	15	10	3/4	Paddle	Black Nylon	0.379"	0.500"	Screw	FN, NN, Sc	H-11 J
35-178	10	On		Off	SPST	20	20	**	Paddle	Black Plastic	0.342"	0.500"	QC .250"/Sd	N, BFN	H-11 K
35-3009	5	On		Off	SPST	20	10	1-1/2	Paddle	Black Nylon	0.280"	0.500"	QC .250"/Sd	KN	H-11 E
35-3150	8	On	Off	On	SPDT	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	QC .250"	FN, NN	H-11 I
35-3154	8	On		Off	DPST	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	QC .250"	FN, NN	H-11 I
35-3156	8	On		On	DPDT	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	QC .250"	FN, NN	H-11 I
35-3158	8	On	Off	On	DPDT	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	QC .250"	FN, NN	H-11 I
35-3160	9	On		Off	SPST	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	Screw	FN, NN, Sc	H-11 J
35-3162	9	On		On	SPDT	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	Screw	FN, NN, Sc	H-11 J
35-3164	9	On		Off	DPST	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	Screw	FN, NN, Sc	H-11 J
35-3168	9	On	Off	On	DPDT	20*		1-1/2	Paddle	Black Nylon	0.379"	0.500"	Screw	FN, NN, Sc	H-11 J

Notes: (On) = Momentary On

*Rated 20A @ 125-277VAC

BFN = Brass Face Nut

FN = Face Nut

HP = Horse Power

ID = ID Plate

KN = Knurled Nut

NN = Nickel Nut

N = Nut(s)

QC = Quick Connect

Sc = Screw

Sd = Solder

WL = Wire Lead

† = Reversing Toggle

** = 1/2 HP@125V, 1 HP@250V

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.