

MINIATURE TOGGLES




Fig. 1



Fig. 2




Fig. 3




Fig. 4

Miniature Toggles with Printed Circuit Board Right Angle Vertical Mount Terminals

Retail Part No.	Figure No.	Circuit Function			Poles/Throws	125VAC/28VDC	AMPS 250VAC	Actuator Style	Actuator Material	Bushing Length	Mounting Hole	Terminal Type	Spec. Drawing Page No.
35-104	1	On	Off	On	SPDT	5	2	Bat	BCP	0.350"	0.250"	PCB††	H-7 A
35-107	2	On		On	DPDT	5	2	Bat	BCP	0.350"	0.250"	PCB††	H-7 B
35-108	2	On		(On)	DPDT	5	2	Bat	BCP	0.350"	0.250"	PCB††	H-7 B

Miniature Toggles with Printed Circuit Board Right Angle Horizontal Mount Terminals

Retail Part No.	Figure No.	Circuit Function			Poles/Throws	125VAC/28VDC	AMPS 250VAC	Actuator Style	Actuator Material	Bushing Length	Mounting Hole	Terminal Type	Spec. Drawing Page No.
35-115	3	On		On	SPDT	5	2	Bat	BCP	0.350"	0.250"	PCB†††	H-7 C
35-125	3	(On)	Off	(On)	SPDT	5	2	Bat	BCP	0.350"	0.250"	PCB†††	H-7 C
35-127	4	On		On	DPDT	5	2	Bat	BCP	0.350"	0.250"	PCB†††	H-7 D
	4	(On)	Off	(On)	DPDT	5	2	Bat	BCP	0.350"	0.250"	PCB†††	H-7 D

Notes: (On) = Momentary On
BCP = Brass Chrome Plate

KN = Knurled Nut
LR = Lock Ring

LW = Lock Washer
N = Nut(s)

PCB = Printed Circuit Board
PCB† = Printed Circuit Board with Integral Bracket
QC = Quick Connect
PCB†† = Printed Circuit Board Right Angle Vertical Mount
PCB††† = Printed Circuit Board Right Angle Horizontal Mount

MEDIUM DUTY TOGGLES

H



Fig. 5



Fig. 6



Fig. 7



Fig. 8

Retail Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	AMPS 12VDC	HP 125-250VAC	Actuator Style	Color	Bushing Length	Mounting Hole	Terminal Type	Hardware	Spec. Drawing Page No.
35-090	5	On	Off	SPST				16		Paddle*	Red	0.342"	0.500"	QC .250"	N, LN	H-7 E
35-092	5	On	Off	SPST				16		Paddle*	Green	0.342"	0.500"	QC .250"	N, LN	H-7 E
35-094	5	On	Off	SPST				16		Paddle*	Amber	0.342"	0.500"	QC .250"	N, LN	H-7 E
35-3008	6	On	Off	SPST		15	10		3/4	Paddle	Black		0.550" x 1.125"	QC .250"	N, LN	H-7 F
35-3091	7	On	Off	SPST		15	10		3/4	Paddle**	Amber		0.550" x 1.125"	QC .250"	N, LN	H-7 F
35-3140	8	On	Off	SPST		15	10		3/4	Paddle*	Red/Green	0.379"	0.500"	QC .250"	N, LN	H-7 G

Notes: *Lighted Paddles (12V Incandescent)
**Lighted Base (125 V Neon)

FN = Face Nut
HP = Horse Power

LN = Locking Nut
N = Nut

QC = Quick Connect

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.