

GENERAL PURPOSE SNAP ACTION (Cont.)



Fig. 1



Fig. 2

Retail Part No.	Figure No.	Amps **VAC	Amps 125 VDC	Amps 250 VDC	HP 125 VAC	HP 250 VAC	PT Max. (In)	OT Min. (In)	DT Max. (In)	OF Max. Oz. (grams)	Actuator	Actuator Length (In)	Terminal Type	Spec. Drawing Page No.
35-3908	1	20	1/2	1/4	3/4	1-1/2	0.025	0.22	0.002	20 (567)	High OT Pl		Sc	H-39 A
35-3916	2	20	1/2	1/4	3/4	1-1/2	0.380	0.190	0.078	2.5-18 (71-510)	Lever	2.34	Sc	H-39 B

Notes: All of the above have momentary action
 **125/250/480VAC
 All have SPDT

DT = Differential Travel
 HP = Horse Power
 HRo = Hinged Roller
 LRo = Leaf Rollers
 LL = Leaf Lever

OF = Operating Force
 OT = Over Travel
 Pb = Pushbuttons
 Pl. = Plunger

PT = Pre-Travel
 OC = Quick Connect
 RP = Roller Plunger
 Sc = Screw
 RARO = Reverse Action Roller

Sd = Solder
 SP = Stub Plunger
 PP = Pin Plunger
 Ro = Roller

KEYLOCK SWITCHES



Fig. 3



Fig. 4



Fig. 5



Fig. 6

Retail Part No.	Figure No.	Poles/Throws	Amps 125 VAC	Action	Index	Lock Type	Key Removal	Actuator	Terminal Type	Mounting Hole (In)	Hardware	Spec. Drawing Page No.
35-3190	3	SPDT	4	On/On	90°	4 tumbler w/detent	2 Pos.	Metal Key†	Sd Lug	0.760 x 0.640	N, 2Keys	H-39 G
35-3192	3	DPDT	4	On/On	90°	4 tumbler w/detent	2 Pos.	Metal Key†	Sd Lug	0.760	N, 2Keys	H-39 G
35-3193	4	SPDT	4	On/On	90°	6 tumbler w/tube lock	2 Pos.	Metal Barrel Key†	6" WL	0.760 x 0.640	N, 2Keys	H-39 H
35-3194	4	SPDT	4	On/On	90°	6 tumbler w/tube lock	1 Pos.	Metal Barrel Key†	6" WL	0.760 x 0.640	N, 2Keys	H-39 H
35-3195	5	SPDT	4	On(On)	45°	4 tumbler	1 Pos.	Metal Key†	6" WL	0.760 x 0.640	N, 2Keys	H-39 F
35-3197	6	SP3T	4	**	45°	4 tumbler	1 Pos.	Metal Key†	Sd Lug	0.760 x 0.640	N, 2Keys	H-39 G

Notes: *Rated @ 2.5Amps 120VAC (480V.A.)

**SP-3 pos. On1 - Off - On2

***Nut, 2 Screws, Ring, and 2 Keys

2.1amps @46VDC (96V.A.), all of the rest are rated @ 2A @250VAC/4A @ 28VDC

Keys (2) included in Hardware

N = Nut

Pos. = Positions

Sc = Screw

Sd = Solder

WL = Wire Leads

† = All keyed alike per figure

#1110801 Keys for 35-3193 & 35-3194

#115140126 Keys for 35-3190, 35-3192, 35-3195 & 35-3197

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.