

LIGHTED APPLIANCE ROCKERS



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10

On-Off Circuit Function

Retail Part No.	Figure No.	Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125 VAC	HP 250 VAC	HP 125-250 VAC	Actuator Color	Actuator Material	Lamp Voltage	Mounting Hole	Spec. Drawing Page No.
35-660	2	SPST	** 10	N/R				Lighted Red		12V Incdt	0.550" x 1.125"	H-25 B
35-696	3	SPST	15	8			1/2	Lighted Red	Nylon	125V Ne	0.508" x 0.756"	H-25 C
35-656	4	SPST	15	10			1/2	Black w/Lighted Amber	Nylon	125V Ne	1.450" x 0.830"	H-25 D
35-662	5	SPST	15	15	1/2	1		Lighted Amber	Nylon	12V Incdt	0.453" x 1.110"	H-25 E
35-664	5	SPST	15	15	1/2	1		Lighted Green	Nylon	12V Incdt	0.453" x 1.110"	H-25 E
35-688	5	SPST	15*	15	1/2	1		Lighted Red	Nylon	125V Ne	0.453" x 1.110"	H-25 A
35-689	6	SPST	15	10			3/4	Lighted Red	Nylon	125V Ne	0.550" x 1.125"	H-25 F
35-3790	6	SPST	15	10			3/4	Lighted Amber	Nylon	125V Ne	0.550" x 1.125"	H-25 F
35-621	7	SPST	16	16				Black w/Red Lens	Plastic	125V Ne	0.870" x 1.070"	H-25 G
35-3730	8	SPST	16	10				Lighted Amber		125V Ne	0.550" x 1.125"	H-25 H
35-3740	8	SPST	16	10				Lighted Red		125V Ne	0.550" x 1.125"	H-25 H
35-655	9	DPST	20	15	N/R	N/R		Lighted Red	Plastic	125V Ne	1.000" x 1.125"	H-25 I
35-686	10	DPST	20	20	1/2	1		Black w/Red Indicator	Plastic	125V Ne	1.180" x 0.870"	H-25 J

Notes: *Built-in Resistor

**Rated 10 Amps @ 30VDC

***Requires external resistor and diode for AC applications (not included)

Incdt = Incandescent

Ne = Neon

N/R = Not Rated

QC = Quick Connect

The Terminal Types for the above parts are QC .250" except for 35-696 is QC .187".

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.