

LIGHTED MINIATURE ROCKERS



Fig. 1



Fig. 2

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function	Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Terminal Type	Mounting Hole	Spec. Drawing Page No.
35-680	35-680-BU	1	On Off	SPST	5	3	Lighted Orange LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-681	35-681-BU	1	On Off	SPST	5	3	Lighted Green LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-682	35-682-BU	1	On Off	SPST	5	3	Lighted Red LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-645	35-645-BU	2	On Off	SPST	10	5	Lighted Red LED	Solder Eyelet	0.755" x 0.508"	H-19 B
35-646	35-646-BU	2	On Off	DPST	10	5	Lighted Red LED	Solder Eyelet	0.755" x 0.508"	H-19 B

Notes: (On)/(Off) = Momentary On/Off
QC = Quick Connect

(In Series) Resistor Chart for 35-680, 35-681 and 35-682 for DC usage (pilot lamp). Diode for AC usage.

Forward	Current	Reverse	Intensity	Recommended Resistor @ Voltage		
V_{FD}	I_{LED}	V_R	M_{CD}	5V	12V	24V
2.1	10	4V	1.6 typ.	270	1K	2.2K

MINIATURE ROCKERS



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function	Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Terminal Type	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-602	35-602-BU	3	On On	SPDT	4	2	Black Plastic	Solder Lug		0.350 x 0.734	H-19 C
35-603	35-603-BU	3	On (On)	SPDT	4	2	Black Plastic	Solder Lug		0.350 x 0.734	H-19 C
35-604	35-604-BU	3	On Off	SPDT	4	2	Black Plastic	Solder Lug		0.350 x 0.734	H-19 C
35-615	35-615-BU	4	On On	SPDT	4	2	Black	QC .187"		0.508 x 0.756	H-19 D
35-605	35-605-BU	5	On Off	SPST	8	4	Black/Red Indicating	QC .187"	Red 0-	0.508 x 0.756	H-19 E
35-606	35-606-BU	6	On On	DPDT	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-608	35-608-BU	6	On Off	DPST	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-609	35-609-BU	6	On On	SPDT	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-674	35-674-BU	7	On On	DPDT	8	4	Red Plastic	Solder Lug		0.625 x 0.523	H-19 F
35-676	35-676-BU	7	On Off	DPDT	8	4	Red Plastic	Solder Lug		0.625 x 0.523	H-19 F
35-642	35-642-BU	8	On Off	SPST	10	6	Black Plastic	QC .250"	White 0-	0.508 x 0.755	H-19 G
35-644	35-644-BU	4	On On	SPDT	10	5	Black	QC .187"		0.508 x 0.756	H-19 D
35-648	35-648-BU	9	On On	DPDT	10	5	Black	QC .187"		0.887 x 0.756	H-19 D
35-607	35-607-BU	6	On Off	SPST	11	N/R	Black	QC .187"		0.508 x 0.756	H-19 E
35-643	35-643-BU	10	On Off	DPST	16*	16	Black Plastic	QC .250"	White 0-	0.483 x 1.021	H-19 H
35-3705		10	On Off	DPST	16	16	White Plastic	QC .250"	Black 0-	0.483 x 1.021	H-19 H

Notes: (On) = Momentary On
*1/4 HP @ 125VAC, 1/2 HP @250VAC
N/R = Not Rated

QC = Quick Connect

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single; BU's are packages of 25 Unless otherwise noted.