

LIGHTED MINIATURE ROCKERS



Fig. 1



Fig. 2

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Terminal Type	Mounting Hole	Spec. Drawing Page No.
35-680	1	On	Off	SPST	5	3	Lighted Orange LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-681	1	On	Off	SPST	5	3	Lighted Green LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-682	1	On	Off	SPST	5	3	Lighted Red LED	QC .187"/Solder	0.512" x 0.750"	H-19 A
35-645	2	On	Off	SPST	10	5	Lighted Red LED	Solder Eyelet	0.755" x 0.508"	H-19 B
35-646	2	On	Off	DPST	10	5	Lighted Red LED	Solder Eyelet	0.755" x 0.508"	H-19 B

Notes: (On)/(Off) = Momentary On/Off

QC = Quick Connect

(In Series) Resistor Chart for 35-680, 35-681 and 35-682 for DC usage (pilot lamp). Diode for AC usage.

Forward	Current	Reverse	Intensity	Recommended Resistor @ Voltage		
V_{FD}	I_{LED}	V_R	M_{CD}	5V	12V	24V
2.1	10	4V	1.6 typ.	270	1K	2.2K

MINIATURE ROCKERS



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Terminal Type	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-603	3	On	(On)	SPDT	4	2	Black Plastic	Solder Lug		0.350 x 0.734	H-19 C
35-615	4	On	On	SPDT	4	2	Black	QC .187"		0.508 x 0.756	H-19 D
35-605	5	On	Off	SPST	8	4	Black/Red Indicating	QC .187"	Red 0-	0.508 x 0.756	H-19 E
35-606	6	On	On	DPDT	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-608	6	On	Off	DPST	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-609	6	On	On	SPDT	8	4	Black	QC .187"		0.508 x 0.756	H-19 E
35-674	7	On	On	DPDT	8	4	Red Plastic	Solder Lug		0.625 x 0.523	H-19 F
35-676	7	On	Off	DPDT	8	4	Red Plastic	Solder Lug		0.625 x 0.523	H-19 F
35-642	8	On	Off	SPST	10	6	Black Plastic	QC .250"	White 0-	0.508 x 0.755	H-19 G
35-644	4	On	On	SPDT	10	5	Black	QC .187"		0.508 x 0.756	H-19 D
35-648	9	On	On	DPDT	10	5	Black	QC .187"		0.887 x 0.756	H-19 D
35-607	6	On	Off	SPST	11	N/R	Black	QC .187"		0.508 x 0.756	H-19 E
35-643	10	On	Off	DPST	16*	16	Black Plastic	QC .250"	White 0-	0.483 x 1.021	H-19 H
35-3705	10	On	Off	DPST	16	16	White Plastic	QC .250"	Black 0-	0.483 x 1.021	H-19 H

Notes: (On) = Momentary On

QC = Quick Connect

*1/4 HP @ 125VAC, 1/2 HP @250VAC

N/R = Not Rated

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.