

## STANDARD APPLIANCE ROCKERS



Fig. 1



Fig. 2



Fig. 3

Retail Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-691	1	On		Off	SPST	16	10	Black	Nylon		0.550" x 1.125"	H-23 A
35-694	1	On	Off	On	SPDT	16	10	Black	Nylon		0.550" x 1.125"	H-23 B

Retail Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125/250VAC	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-3600	2	On		Off	SPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 C
35-3630	2	On		Off	DPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 D
35-3640	2	On		On	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 E
35-3695	2	(On)	Off	(On)	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 F
35-695	3	(On)	Off	(On)	SPDT	16	16	1	Black Plastic		0.550" x 1.180"	H-23 G

Notes: (On) = Momentary On      N/R = Not Rated      † = 20A @ 277VAC and 2 H.P. @ 250VAC  
 \*3/4 H.P. @ 125/250VAC      All of the Above have Quick Connect .250" Terminals

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.