

STANDARD APPLIANCE ROCKERS



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-3760	1	(On)	Off	SPST	15*	10	White	Nylon		0.550" x 1.125"	H-21 A
35-691	2	On	Off	SPST	16	10	Black	Nylon		0.550" x 1.125"	H-21 B
35-693	3	On	Off	SPST	16	10	Black	Nylon	Red On/Off	0.550" x 1.125"	H-21 B
35-694	2	On	Off	SPDT	16	10	Black	Nylon		0.550" x 1.125"	H-21 B
35-3030	3	On	Off	SPST	16*	10	Black	Nylon	Red On/Off	0.550" x 1.125"	H-21 B

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125/250VAC	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-3600	4	On	Off	SPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3610	4	On	On	SPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3620	4	On	Off	SPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3630	4	On	Off	DPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3636	4	On	Off	SPST	20	†	1-1/2	Black Nylon		0.830" x 1.450"	H-21 D
35-3640	4	On	On	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3650	4	On	Off	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3660	4	(On)	Off	DPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3670	4	(Off)	On	DPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3680	4	(On)	On	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3690	4	(On)	Off	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-21 D
35-3695	4	(On)	Off	(On)	DPDT	15	10	3/4	Black Nylon	0.830" x 1.450"	H-21 D
35-3710	4	On	Off	SPST	16	10	3/4	Black Nylon		0.550" x 1.125"	H-21 C
35-3720	4	On	On	SPDT	16	10	3/4	Black Nylon		0.550" x 1.125"	H-21 C

Retail Part No.	Figure No.	Circuit Function		Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 250 VAC	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-620	5	On	Off	DPST	15	10	1/4	Red Poly	White On/Off	0.866" x 1.102"	H-21 E
35-640	6	On	On	SPDT	16	16	1	Black Nylon		1.100" x 0.453"	H-21 F
35-695	7	(On)	Off	(On)	SPDT	16	16	1	Black Plastic	0.550" x 1.180"	H-21 F
35-654	8	On	Off	DPST	20	15	N/R	Black Plastic		1.000" x 1.125"	H-21 G

Notes: (On) = Momentary On N/R = Not Rated † = 20A @ 277VAC and 2 H.P. @ 250VAC
 *3/4 H.P. @ 125/250VAC All of the Above have Quick Connect .250" Terminals

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single unless otherwise noted.