

## Terminals & Connectors (K-Spec® Series)

### PVC Insulated Spade/Fork Terminals (K-Spec® Series)



600V Rating, 75°C, Copper

#### 22-18GA



Stud Size #6  
561048 100 pk  
561048D 500 pk



Stud Size #8  
561049 100 pk  
561049D 500 pk



Stud Size #10  
561050 100 pk  
561050D 500 pk

#### 16-14GA



Stud Size #6  
561061 100 pk  
561061D 500 pk



Stud Size #8  
561062 100 pk  
561062D 500 pk



Stud Size #10  
691063 9 pk  
561063 100 pk  
561063D 500 pk



Stud Size 1/4"  
561064 100 pk  
561064D 500 pk

#### 12-10GA



Stud Size #6  
561074 100 pk  
561074D 500 pk



Stud Size #8  
561075 100 pk  
561075D 500 pk



Stud Size #10  
691076 7 pk  
561076 100 pk  
561076D 500 pk



Stud Size 1/4"  
561077 100 pk  
561077D 500 pk

### Fully Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)



300V Rating, Brass. Nylon (105°C). PVC (75°C)

#### 22-18GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561354 100 pk  
561354D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561353 100 pk  
561353D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
561345 100 pk  
561345D 500 pk

#### 16-14GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561357 100 pk  
561357D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561358 100 pk  
561358D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
561346 100 pk  
561346D 500 pk

#### 12-10GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561623 100 pk  
561623D 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
561621 100 pk  
561621D 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
561347 100 pk  
561347D 500 pk