

# Crimp 'N' Shrink Heat Shrinkable Terminals & Connectors

A

## Spade/Fork Terminals (Crimp 'N' Shrink)



### 22-18GA



Stud Size #8

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 761708 | 25 pk  |
| 761708B            | 500 pk |



Stud Size #10

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691709 | 5 pk   |
| 761709             | 25 pk  |
| 761709B            | 500 pk |

### 16-14GA



Stud Size #8

|         |        |
|---------|--------|
| 761710  | 25 pk  |
| 761710B | 500 pk |



Stud Size #10

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691711 | 5 pk   |
| 761711             | 25 pk  |
| 761711B            | 500 pk |

### 12-10GA



Stud Size #8

|         |        |
|---------|--------|
| 761712  | 25 pk  |
| 761712B | 500 pk |



Stud Size #10

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691713 | 5 pk   |
| 761713             | 25 pk  |
| 761713B            | 500 pk |

## Quick Disconnects/Slide Connectors (Crimp 'N' Shrink)



### 22-18GA


Female quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691714 | 5 pk   |
| 761714             | 25 pk  |
| 761714B            | 500 pk |


Male quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691715 | 5 pk   |
| 761715             | 25 pk  |
| 761715B            | 500 pk |

### 16-14GA


Female quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691655 | 5 pk   |
| 761655             | 25 pk  |
| 761655B            | 500 pk |


Male quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691656 | 5 pk   |
| 761656             | 25 pk  |
| 761656B            | 500 pk |

### 12-10GA


Female quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691658 | 5 pk   |
| 761658             | 25 pk  |
| 761658B            | 500 pk |


Male quick disconnect  
Fully Insulated, Tab Size 0.25"

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691657 | 5 pk   |
| 761657             | 25 pk  |
| 761657B            | 500 pk |

## Bullet Connectors (Crimp 'N' Shrink)




### 16-14GA


Female Snap Receptacle  
0.156" (3.97mm)

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691660 | 5 pk   |
| 761660             | 25 pk  |
| 761660B            | 500 pk |


Male Snap Plug  
0.156" (3.97mm)

|                    |        |
|--------------------|--------|
| <b>*NEW</b> 691659 | 5 pk   |
| 761659             | 25 pk  |
| 761659B            | 500 pk |


Female Snap Receptacle  
0.180" (4.57mm)

|                     |        |
|---------------------|--------|
| <b>*NEW</b> 761665  | 25 pk  |
| <b>*NEW</b> 761665B | 500 pk |


Male Snap Plug  
0.180" (4.57mm)

|                     |        |
|---------------------|--------|
| <b>*NEW</b> 761664  | 25 pk  |
| <b>*NEW</b> 761664B | 500 pk |

Crimp Tools for Heat Shrink Terminals can be found on page 15. Heating tools are on pages 126-127