

FULLY INSULATED FEMALE DISCONNECTS NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C



Part #	AWG	COLOUR	TAB SIZE
CFR4NA250F	22-18	RED	.250"
CFR4NA187F	22-18	RED	.187"
CFR4NB250F	16-14	BLUE	.250"
CFR4NB187F	16-14	BLUE	.187"
CFR4NC250F	12-10	YELLOW	.250"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: RAT-FIDISC, 453, HTS1000



Terminals are NOT Actual Size See Sizing Chart on B-38, B-39

FULLY INSULATED MALE DISCONNECTS NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C


Part #	AWG	COLOUR	TAB SIZE
CM4TNA250F	22-18	RED	.250"
CM4TNA187F	22-18	RED	.187"
CM4TNB250F	16-14	BLUE	.250"
CM4TNB187F	16-14	BLUE	.187"
CM4TNC250F	12-10	YELLOW	.250"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: RAT-FIDISC, 453, HTS1000



FULLY INSULATED FEMALE FLAG DISCONNECTS - NYLON SINGLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C


Part #	AWG	COLOUR	TAB SIZE
FLFR6A250F	22-18	RED	.250"
FLFR6B250F	16-14	BLUE	.250"
FLFR6C250F	12-10	YELLOW	.250"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: RAT-FLAG (Red, Blue)



FULLY INSULATED FEMALE FLAG DISCONNECTS - NYLON DOUBLE CRIMP

For use with Copper Stranded Wire Only

Rated at 105°C



Part #	AWG	COLOUR	TAB SIZE
FLFR6A250BF	22-18	RED	.250"
FLFR6B250BF	16-14	BLUE	.250"
FLFR6C250BF	12-10	YELLOW	.250"

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack (Quantities vary by Part #)

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: -RAT-FLAG (Red, Blue)



Extra Brass Ring Crimps Wire Insulation

Copper Stranded Wire Only