



STAINLESS STEEL LIQUIDTIGHT CONNECTORS

Rated IP68 and NEMA 4X, Remke Stainless Steel Liquidtight Connectors offer all the corrosion resistance you need AND the strength of stainless steel for the highest levels of endurance. Additional features of these connectors include:


- Used to connect liquidtight conduit into a knockout or threaded NPT opening
- For use in wet or dry locations to seal electrical connections against dust, dirt, oil, water, chemicals and other corrosive elements
- Type 304 stainless steel body and ferrule
- Available in straight and 90 degree, 3/8" to 2" in stock
- Nylon insulated throat
- Viton® O-Ring standard (optional from other manufacturers)

Remke Stainless Steel Liquidtight Connectors are ideally suited for OEM and MRO applications known for their corrosive and abusive environments including:

- Food & Beverage Processing
- Petrochemical
- Pulp & Paper Mills
- Wastewater Treatment
- Heavy-duty electrical motors, generators and transformers
- Offshore Oil Rigs & Platforms
- Chemical Processing
- Portable equipment
- Machine Tool Building




STRAIGHT STAINLESS STEEL LIQUIDTIGHT CONNECTORS



PART NUMBERS

Conduit Size	Catalog Number	Thread Length (A)	Body Hex (B)	Dia. Across Flats (C)
3/8"	LMSS-01	0.45	0.94	1.02
1/2"	LMSS-11	0.51	1.06	1.14
3/4"	LMSS-21	0.59	1.30	1.38
1"	LMSS-31	0.59	1.69	1.77
1 1/4"	LMSS-41	0.63	2.04	2.12
1 1/2"	LMSS-51	0.71	2.36	2.44
2"	LMSS-61	0.79	2.93	3.03

90 DEGREE STAINLESS STEEL LIQUIDTIGHT CONNECTORS



PART NUMBERS

Conduit Size	Catalog Number	Thread Length (A)	Body Hex (B)	Dia. Across Flats (C)
3/8"	LMSS-01-90	0.45	0.94	1.02
1/2"	LMSS-11-90	0.51	1.06	1.14
3/4"	LMSS-21-90	0.59	1.30	1.38
1"	LMSS-31-90	0.59	1.69	1.77
1 1/4"	LMSS-41-90	0.63	2.04	2.12
1 1/2"	LMSS-51-90	0.71	2.36	2.44
2"	LMSS-61-90	0.79	2.93	3.03

SPECIFICATIONS

MATERIALS

Body and Cap	304 Stainless Steel
Ferrule	304 Stainless Steel
O-Ring	Viton®
Protection	IP68, NEMA 4X
Listings	UL Listed, CSA Certified RoHS Compliant