



STANDARD CABLE TIES

A

**PLENUM
RATING
AH-2**

 See
page A-32 for
mil-specs

Intermediate 30lb, 40lb Natural, UV Black

Per Bag	Part no.	Colour & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case	ANSI/UL 62275 TYPE
1,000	L-5409M	Natural Nylon	5.84/148.33	.140/3.556	.049/1.244	40lb	1.437/36.512	UL-CSA MS3367-S*	10,000	21
100	L-5409C	Nylon								
1,000	L-5400M	UV Black Nylon	5.84/148.33	.140/3.556	.049/1.244	40lb	1.437/36.512	UL-CSA MS3367-S*	10,000	21
100	L-5400C	Nylon								
1,000	L-8409M	Natural Nylon	8.875/225.42	.140/3.556	.049/1.244	40lb	2.375/60.325	UL-CSA	10,000	21
100	L-8409C	Nylon								
1,000	L-8400M	UV Black Nylon	8.875/225.42	.140/3.556	.049/1.244	40lb	2.375/60.325	UL-CSA	10,000	21
100	L-8400C	Nylon								
100	L-11409C	Natural Nylon	11.56/293.67	.140/3.556	.058/1.473	40lb	3.375/85.72	UL-CSA	5,000	21
100	L-11400C	UV Black Nylon								
100	L-14409C	Natural Nylon	14.50/368.30	.140/3.556	.058/1.473	40lb	4.00/101.60	UL-CSA	5,000	21
100	L-14400C	UV Black Nylon								

 Tolerance: .XXX = ± 0.005 , .XX = ± 0.015 , Fraction = $\pm 1/32$ "

**PLENUM
RATING
AH-2**

Standard 50lb Natural, UV Black

Per Bag	Part no.	Colour & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case	ANSI/UL 62275 TYPE
1,000	L-7509M	Natural Nylon	7.56/192.07	.180/4.572	.052/1.320	50lb	1.875/47.625	UL-CSA MS3367-1*	10,000	21S
100	L-7509C	Nylon								21S
1,000	L-7500M	UV Black Nylon	7.56/192.07	.180/4.572	.052/1.320	50lb	1.875/47.625	UL-CSA MS3367-1*	10,000	21S
100	L-7500C	Nylon								21S
500	L-11509D	Natural Nylon	11.25/285.75	.180/4.572	.052/1.320	50lb	3.062/77.787	UL-CSA MS3367-7*	5,000	21S
100	L-11509C	Nylon								21S
500	L-11500D	UV Black Nylon	11.25/285.75	.180/4.572	.052/1.320	50lb	3.062/77.787	UL-CSA MS3367-7*	5,000	21S
100	L-11500C	Nylon								21S
500	L-14509D	Natural Nylon	14.56/369.87	.180/4.572	.052/1.320	50lb	4.125/104.775	UL-CSA MS3367-2*	5,000	21S
100	L-14509C	Nylon								21S
500	L-14500D	UV Black Nylon	14.56/369.87	.180/4.572	.052/1.320	50lb	4.125/104.775	UL-CSA MS3367-2*	5,000	21S
100	L-14500C	Nylon								21S
100	L-17509C	Natural Nylon	17.09/434.16	.187/4.749	.060/1.524	50lb	4.75/120.65	UL	5,000	21
100	L-17500C	UV Black Nylon								21

 Tolerance: .XXX = ± 0.005 , .XX = ± 0.015 , Fraction = $\pm 1/32$ "

 MADE IN  U.S.A.

**NOW
21S!**