

Push Button Control Stations – Plastic

Plastic Operating Heads for Control Stations & Dimensions



PB-BG2P

C



PB-BE101BP

Plastic Operating Heads for Key Switches – IP 65 for use with RC●P & RC●M enclosures – IP65

Description	Type	Key removal	Reference
2 Position	Stay Put	LH Position	PB-BG2P
		RH Position	PB-BG02P
		All Positions	PB-BG4P
3 Position	Stay Put	Centre Position	PB-BG3P
		LH and RH Position	PB-BG5P
		All 3 Positions	PB-BG0P
		RH Position	PB-BG09P
		LH Position	PB-BG9P
	Both Side Spring Return To Centre	Centre Position	PB-BG7P
	Stay Put To Left Spring Return From Right To Centre	Centre Position	PB-BG8P

Contact Blocks (Base Mounted) for use with RC●P enclosures – IP65

Description	Contact	Type	Reference
Contact Blocks	NO	Standard	PB-BE101BP
	NC	Standard	PB-BE102BP

Dimensions

	Plastic				Metal			
	1 Hole (inch/mm)	2 Hole (inch/mm)	3 Hole (inch/mm)	4 Hole (inch/mm)	1 Hole (inch/mm)	2 Hole (inch/mm)	3 Hole (inch/mm)	4 Hole (inch/mm)
H	2.1" / 51	2.1" / 51	2.1" / 51	2.1" / 51	2.1" / 51	2.1" / 51	2.1" / 51	2.1" / 51
W	2.68" / 68	2.68" / 68	2.68" / 68	2.68" / 68	2.68" / 68	2.68" / 68	2.68" / 68	2.68" / 68
L	2.91" / 74	4.09" / 104	5.28" / 134	6.46" / 164	2.91" / 74	4.13" / 105	5.28" / 134	6.46" / 164
W1	2.13" / 54	2.13" / 54	2.13" / 54	2.13" / 54	2.13" / 54	2.13" / 54	2.13" / 54	2.13" / 54
L1	1.5" / 38	2.68" / 68	2.68" / 68	5.04" / 128	1.31" / 46	3.07" / 78	4.25" / 108	5.43" / 138

